

ICOM

IC-M94D

VHF MARINE TRANSCEIVER WITH DSC & AIS



AIS Traffic Info, Now in Your Hand

- ▶ AIS Receiver and Class-H DSC in One Package



AIS screen



DSC ACK screen

- ▶ 6 W RF Output Power
- ▶ Class-Leading 1500 mW Audio Output Power
- ▶ Simplified Navigation Functions
- ▶ 10 Hours (approx.) of Long-Lasting Battery Life*
- ▶ Float'n Flash and MOB Auto-Activation

* Typical operation with 5:5:90 duty ratio.

AIS Receiver and DSC in One Package

AIS receiver and DSC function add further assurance for safety at sea. With the integrated AIS receiver, vessel traffic information is shown on the display. The AIS target call function allows you to easily set up a DSC individual call. Distress calls can be made with the rear panel button.



DISTRESS button

6 W RF Output Power and 10 Hours of Operating Time

The IC-M94D's 6 watts of transmit power provides extended communication range for the user. The supplied 2400 mAh (typical) high capacity Li-ion battery, BP-306 provides 10 hours of operating time, under normal conditions*.

*Approximate, typical operation with 5:5:90 duty ratio.

Class-Leading 1500 mW Audio Output

Icom's custom high-power capacity speaker delivers a loud 1500 mW (typical) audio output with improved acoustic sound clarity for noisy maritime environments.

Simplified Navigation Function

The Navigation function guides you to a specified waypoint. You can assign up to 50 favorite fishing spots or destinations as waypoints.



Navigation screen

Float'n Flash and MOB Auto Set Functions

The radio floats and the LCD screen, keys and rear panel Distress button flash to help you retrieve it from the water. Pressing the distress button while Float'n Flash is working will transmit the MOB distress signal, rather than the plain undesigned one for better protection of sailors.

And More

- Integrated GPS receiver
- Active noise canceling technology
- IPX7 submersible (1 m depth of water for 30 minutes)
- Weather channel receive (for USA version)
- Dualwatch and Tri-watch functions
- Favorite channel function
- AquaQuake™ prevents audio degradation from a water-logged speaker
- Supports 4-digit channels

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

RECHARGEABLE Li-ion BATTERY PACK BP-306 Li-ion 7.2 V, 2280 mAh (minimum) 2400 mAh (typical)	DESKTOP CHARGER BC-251 Charges the BP-306 (in the radio) in 3.5 hours (approx.). Same as supplied.	AC ADAPTER BC-242 Use with BC-251.	SPEAKER-MICROPHONES HM-228 IPX7 compact type HM-165 IPX7 rugged type Floats in water with the radio.
LEATHER BELT HANGERS MB-96FL Long fixed type MB-96F Fixed type	CIGARETTE LIGHTER CABLE CP-25H For use with BC-251 Equivalent to the supplied CP-26.	ANTENNA FA-SC59V Same as supplied	BELT CLIP MB-133 Same as supplied

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

SPECIFICATIONS

GENERAL

Frequency range	TX	156.025–157.425 MHz
	RX	156.050–163.275 MHz
	DSC	156.525 MHz
	AIS (RX)	162.025 MHz
Usable channel groups		INT, USA, CAN, WX channels
Type of emission		16K0G3E (FM), 16K0G2B (DSC) 16K0GXW (AIS)
Current drain (at 7.2 V DC)		
TX (6 W/1 W output)		1500 mA/700 mA (approx.)
RX (Inter SP/Exter SP Max. audio)		700 mA/350 mA (approx.)
Operating temperature range		-20°C to +60°C; -4°F to +140°F
Antenna impedance		50 Ω
Dimensions (W×H×D) (projections not included)		60.9 × 145.8 × 43.8 mm; 2.4 × 5.7 × 1.7 in
Weight (approximate)		357 g ; 12.6 oz (With BP-306, antenna, MB-133)

TRANSMITTER

Output power (Hi/Low)	6 W/1 W
Max. frequency deviation	±5 kHz
Frequency stability	±10 ppm
Spurious emissions	-68 dBc typical

RECEIVER

Sensitivity (at 12 dB SINAD)	0.25 µV typical
DSC receiver (at 1% BER)	-3 dBµ emf typical
AIS receiver (at 20% PER)	-107 dBm
Squelch sensitivity (Threshold)	0.25 µV typical
Adjacent channel selectivity	70 dB typical
DSC receiver (at 1% BER)	73 dBµ emf
Spurious response	70 dB typical
DSC receiver (at 1% BER)	73 dBµ emf
Intermodulation	70 dB typical
DSC receiver (at 1% BER)	68 dBµ emf
Hum and noise	40 dB
Audio output power Internal SP	1500 mW typical (8 Ω load)
(at 10% distortion)	350 mW typical (8 Ω load)

Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	—
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard

Water IPX7 (Submersible protection)

Supplied accessories:

- BP-306 battery pack
- BC-251 battery charger
- AC adapter*
- CP-26 cigarette lighter cable
- MB-133 belt clip
- Antenna
- Hand strap

* May differ depending on version.

Your local distributor/dealer:

Icom America Inc.
www.icomamerica.com

Icom Canada
www.icomcanada.com

Icom Brazil
E-mail: sales@icombrazil.com

Icom (Europe) GmbH
www.icom-europe.com

Icom Spain S.L.
www.icomspain.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Icom Asia Co., Ltd.
www.icomasia.com

www.icomjapan.com

Count on us!