




PRODUCT-DETAILS

XT5N 400 Ekip Dip L SIG In=400 4p F F

XT5N 400 Ekip Dip L SIG In=400 4p F F



General Information	
Extended Product Type	XT5N 400 Ekip Dip L SIG In=400 4p F F
Product ID	1SDA100404R1
EAN	8056221004817
Catalog Description	XT5N 400 Ekip Dip L SIG In=400 4p F F
Long Description	C.BREAKER TMAX XT5N 400 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP L SIG R 400

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2354
Environmental Product Declaration - EPD	9AKK108468A1899 9AKK108468A9748
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 59.6 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	7b429f14-1658-4bd6-9e7c-5a8ecdb60454 Italy (IT)
Simplified SCIP	69875321-56e7-4f3f-9e8c-128dc49b9ecd Netherlands (NL) 16332837-5aa4-4c33-ad55-e9418e3cab54 Germany (DE) 4568461f-4461-407b-88d9-0c77d460193e Croatia (HR) 25ece787-a0d4-434a-b241-a4115d013723 Poland (PL) ec4aa935-3093-4541-b351-a81a5c29efa8 Czech Republic (CZ) 2e2ce8c8-fccb-48e9-8dbf-7b9ef744c45f Belgium (BE) 052d3a34-61ba-48ad-9809-795e4af193fa Germany (DE) 3745f9a2-b650-4254-b644-b3a6867a2e98 Denmark (DK) d2ca4cf0-4c0e-4fd3-b871-90d4a8ac289c Germany (DE) 436369c6-622d-4a78-becf-92af22131f37 Belgium (BE) 53b607bb-d779-447a-b27c-3c90f9a1a298 Spain (ES) 83477e4f-3df2-4fac-9ded-fb46b39b6999 France (FR) b77aa772-9883-4d9e-acd8-bce8a51a4ed8 Germany (DE) 46d12605-c1e8-46de-8ef1-713b93ce9852 Hungary (HU) 3e38f866-d4a2-443e-9180-c32387e031a8 Bulgaria (BG) e511376d-2975-48c2-bf44-a99bbf88e03f Germany (DE) cabdb8c1-4339-479c-8c48-7951fcea47ac France (FR) f148aac3-3588-4dc9-ac82-17f6b042ff01 Sweden (SE) e6c0ab9c-18f0-4e1d-942d-7862e8b1727e Sweden (SE) a32650e8-f87d-4030-9661-ca3e2e5ac5bb Poland (PL) 35df29e6-2473-42ce-a0aa-2e52fe14a334 Portugal (PT) 1b12a987-be05-4f7b-a203-a63e5d2e0dc1 Estonia (EE) d2885aa7-95ad-4e9c-9494-20361b6fd119 Greece (GR) c84bd338-60a5-4155-bb1d-5882a0ab9240 Hungary (HU) 614366c1-f989-4fca-824d-2e06986d410e Poland (PL) 54ed9246-66d3-4dad-a97d-e2e09765d6b5 Finland (FI) ac548716-8862-47d2-a620-1899f8f84795 Norway (NO)

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT5NE440AGFF000XXX
EAN	8056221004817
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	6.4 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	250 mm
Package Level 1 Height	245 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.888 kg
Package Level 1 EAN	8056221004817

Additional Information	
Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH002065A1183 1SDH002065A1131

Technical	
Current Type	AC
Electrical Durability	7000 cycle 60 cycles per hour
Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4P
Order Multiple	1 piece
Power Loss	19 W
Rated Current (I_n)	400 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA

	(500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA
Rated Uninterrupted Current (I _u)	400 A
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

