



PRODUCT-DETAILS

# BMSDW240

## Switch Disconnecter



General Information	
Extended Product Type	BMSDW240
Product ID	1SYD672062R0040
EAN	8906176431629
Catalog Description	Switch Disconnecter
Long Description	The SD BMSDW240 disconnects the power and acts as a Switch. This product is manufactured according to IEC Standards for the markets where it is required.

Technical	
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Rated Current (I <sub>n</sub> )	40 A
Rated Conditional Short-Circuit Current (I <sub>nc</sub> )	6 kA
Rated Frequency (f)	50/60 Hz
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle
Number of Poles	2P

Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Flexible 35 mm² Flexible Solid;25 mm²

Material Compliance

RoHS Status	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	Product Not in WEEE Scope

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20
Pollution Degree	2

Dimensions

Product Net Width	34.8 mm
Product Net Height	88.5 mm
Product Net Depth / Length	74.8 mm
Product Net Weight	0.139 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	149 g

Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A0984
--------------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108469A4847
-----------------------------------	-----------------

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Formula Din Rail → Switch Disconnectors, Formula Din Rail

