




PRODUCT-DETAILS

XT5D 400 4p F F

XT5D 400 4p F F



General Information	
Extended Product Type	XT5D 400 4p F F
Product ID	1SDA100548R1
EAN	8056221006248
Catalog Description	XT5D 400 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT5D 400 FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group	UL 2799 Zero Waste To Landfill Validation available
Waste To Landfill Target	
End Of Life	9AKK108468A2353
Disassembling	
Instructions	
Environmental Product	9AKK108468A9746
Declaration - EPD	9AKK108468A1893
Recyclability Rate of the	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Product acc. to EN45555	

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	3d18b1f4-4d08-4643-b3a9-f7162aec4b52 Italy (IT)
Simplified SCIP	515fae19-d5a1-4c9d-bfd5-7150013e78dc France (FR) f9fcc9e8-e30d-4774-ba61-0f244abb42a7 Greece (GR) 38d310c0-63d4-4423-9a8d-799701e9ca16 Germany (DE) 60ce7c87-9c46-4138-a2c3-1753a7ef888e Finland (FI) b77336b9-c285-4ec0-8eae-329474e23b67 Hungary (HU) 63601c75-41ed-4206-80a2-7de275c81b81 Netherlands (NL) 0a555105-8471-4a70-af4c-8b07c080eba2 Sweden (SE) 71e0c04e-df95-48f8-801f-e507c7e0619a Germany (DE) 015b7f0b-579a-4f74-ad7a-f1dd6bee7108 Portugal (PT) f38f9f6c-2841-48ff-a64b-ccfc16d80025 Germany (DE) 91ee2f17-828a-4814-94a3-bc834f0ad9bc Poland (PL) 015b7f0b-579a-4f74-ad7a-f1dd6bee7108 Portugal (PT) f9fcc9e8-e30d-4774-ba61-0f244abb42a7 Greece (GR) a9445c33-1800-49bd-ad8f-ddbfac187b18 Germany (DE) 84f1e865-66ae-4e00-a5ed-44780ad5ea77 Poland (PL) f38f9f6c-2841-48ff-a64b-ccfc16d80025 Germany (DE) 71e0c04e-df95-48f8-801f-e507c7e0619a Germany (DE) e136e2ce-35f6-456f-afb9-2c2388c709ab Spain (ES) aae2e110-77ea-4db8-977b-3bc59204476d France (FR) f19452ee-00f8-448d-b689-7cc7915a2713 Hungary (HU) b77336b9-c285-4ec0-8eae-329474e23b67 Hungary (HU) 61217bed-bf27-4dce-91e9-e73db4756400 Estonia (EE) aae2e110-77ea-4db8-977b-3bc59204476d France (FR) 91ee2f17-828a-4814-94a3-bc834f0ad9bc Poland (PL) f19452ee-00f8-448d-b689-7cc7915a2713 Hungary (HU) c4b6826b-b6bf-4324-9e05-0f2a9ece7770 Croatia (HR) ec7e07d3-f738-4f6d-a734-bec5320ab392 Czech Republic (CZ) 63601c75-41ed-4206-80a2-7de275c81b81 Netherlands (NL) c17f2616-f7a6-4bcb-99bc-80d9a985600e Bulgaria (BG) 515fae19-d5a1-4c9d-bfd5-7150013e78dc France (FR) 01bac6da-cdc9-40cb-a0e7-8a534c2bbe67 Sweden (SE) aa3e606e-eb21-4e5b-9b99-47c77fc221dd Poland (PL) 0a555105-8471-4a70-af4c-8b07c080eba2 Sweden (SE) e136e2ce-35f6-456f-afb9-2c2388c709ab Spain (ES) 34ca218e-e643-435f-8571-3b099d355aba Belgium (BE) 61217bed-bf27-4dce-91e9-e73db4756400 Estonia (EE) 0746af35-681d-4bc2-b5ec-4609e3a0eaa2 Belgium (BE) 60ce7c87-9c46-4138-a2c3-1753a7ef888e Finland (FI) 38d310c0-63d4-4423-9a8d-799701e9ca16 Germany (DE) f2d07ccb-a874-4b5f-ba1e-270431a75952 Germany (DE) 01bac6da-cdc9-40cb-a0e7-8a534c2bbe67 Sweden (SE) a9445c33-1800-49bd-ad8f-ddbfac187b18 Germany (DE) ec7e07d3-f738-4f6d-a734-bec5320ab392 Czech Republic (CZ) aa3e606e-eb21-4e5b-9b99-47c77fc221dd Poland (PL) 34ca218e-e643-435f-8571-3b099d355aba Belgium (BE) 1f9ccb0e-bbd8-4434-98fe-32035a458f6d Norway (NO) 0746af35-681d-4bc2-b5ec-4609e3a0eaa2 Belgium (BE) f2d07ccb-a874-4b5f-ba1e-270431a75952 Germany (DE) b9837d3d-eb64-4f6d-97db-ee272ad708b0 Denmark (DK) c17f2616-f7a6-4bcb-99bc-80d9a985600e Bulgaria (BG) b9837d3d-eb64-4f6d-97db-ee272ad708b0 Denmark (DK) 84f1e865-66ae-4e00-a5ed-44780ad5ea77 Poland (PL) 1f9ccb0e-bbd8-4434-98fe-32035a458f6d Norway (NO) c4b6826b-b6bf-4324-9e05-0f2a9ece7770 Croatia (HR)

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT5DE440ADFF000XXX
E-Number (Norway)	4380446
EAN	8056221006248
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.6 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.088 kg
Package Level 1 EAN	8056221006248

Additional Information

Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Version	F
CAD Dimensional Drawing	1SDH002065A1183 1SDH002065A1131

Technical

Electrical Durability	7000 cycle 60 cycles per hour
Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4P
Order Multiple	1 piece
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage	1000 V

(U _i)	
Rated Operational Current AC-23A (I _e)	(400 V) 400 A (690 V) 400 A
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw})	5 kA
Rated Uninterrupted Current (I _u)	400 A
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

External Classifications and Standards

ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

