



PRODUCT-DETAILS

XT5D 400 3p F F
XT5D 400 3p F F



| General Information | |
|----------------------------|---|
| Extended Product Type | XT5D 400 3p F F |
| Product ID | 1SDA100546R1 |
| EAN | 8056221006224 |
| Catalog Description | XT5D 400 3p F F |
| Long Description | SWITCH-DISCONNECTOR TMAX XT5D 400 FIXED THREE-POLE WITH FRONT TERMINALS |

| ABB EcoSolutions | |
|---|---|
| ABB EcoSolutions | Yes |
| ABB Site Meeting Group Waste To Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
| End Of Life Disassembling Instructions | 9AKK108468A2353 |
| Environmental Product Declaration - EPD | 9AKK108468A9746 9AKK108468A1893 |
| Recyclability Rate of the Product acc. to EN45555 | Design for Closing Resource Loops - Standard EN45555 - 59.6 % |

Material Compliance

| | |
|---|--|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |
| SCIP | 045f2cf1-be91-4bcd-b731-887c182e83ea Italy (IT) |
| Simplified SCIP | 01556332-ded2-46e1-9b05-5bac73208121 Germany (DE) eca2a49d-5ad5-4433-9d0b-ae19f16d4e1e Netherlands (NL) dffb741f-f5c2-479b-9106-31c31ef4ba06 Spain (ES) 6db88e9e-6479-44af-b0b8-e0992f955076 Netherlands (NL) 258fdcfb-4302-4ea1-a8a1-7f689f5848a9 Germany (DE) b76a69cc-0ba2-4ce6-a88f-d186d6966edb Poland (PL) 33c28849-7754-420d-b8c6-f0ccd6b8478a Norway (NO) 22dbb777-bf42-4d24-b54c-a33d1ef48256 Finland (FI) cc90bdc9-48d5-47fe-8df3-adfc2441d412 Netherlands (NL) bf889582-80b0-49a5-9d4a-da0ae1270d58 Germany (DE) 920585fb-c0f9-4371-9465-4fdf58eb943c Denmark (DK) 2da870f5-97d8-4cab-8f69-149222185209 Croatia (HR) bc285540-b9a2-4b97-b115-6f6facc2c63a Czech Republic (CZ) 2bc3ddfb-c0b7-4ba1-832a-334db1e85f80 Poland (PL) ae596363-cc3a-4281-ab4b-bdd592d898ba Netherlands (NL) 105bada4-2430-485d-b15c-1103f09a8efc Netherlands (NL) 5b1492c2-10b7-4d22-a2ba-8fdff2fc7c60 Estonia (EE) 87d124d6-f585-4b1b-b84c-9bf107adccde Portugal (PT) 2faf0f7f-1867-4b9d-a79d-316ffc75e19 Bulgaria (BG) 1b48d7d0-a21e-4f4a-90df-4ac8e1dd4efd Sweden (SE) 29174ac2-3ba6-4cb6-85b4-21b8b9223727 Poland (PL) f7397b96-d7c2-48ef-b3ad-8111935e8936 France (FR) fc258431-4cd3-4234-a135-b43d565660b3 Sweden (SE) 0a5b42b9-53bb-44c0-9816-693d5c0c3532 Greece (GR) 6fb9b86c-8590-43e0-916b-4810ed98fa78 Germany (DE) Od8844a6-9003-453b-8076-a44f2f970364 Germany (DE) 8fb7fda3-253d-427e-9d0b-e7bf2da3f504 France (FR) |

Environmental

| | |
|---------------------------|-----------------|
| Environmental Information | 9AKK108467A6707 |
|---------------------------|-----------------|

Ordering

| | |
|--------------------------|--------------------|
| Order Code US and Canada | XT5DE340ADFF000XXX |
| E-Number (Norway) | 4380321 |
| EAN | 8056221006224 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 140 mm |
| Product Net Height | 205 mm |
| Product Net Depth / Length | 103.5 mm |

Product Net Weight 4.775 kg

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 248 mm |
| Package Level 1 Height | 240 mm |
| Package Level 1 Depth / Length | 285 mm |
| Package Level 1 Gross Weight | 5.263 kg |
| Package Level 1 EAN | 8056221006224 |

Additional Information

| | |
|-------------------------|------------------------------------|
| Product Main Type | SACE Tmax XT |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | Switch Disconnecter |
| Version | F |
| CAD Dimensional Drawing | 1SDH002065A1115 1SDH002065A1131 |

Technical

| | |
|---|------------------------------------|
| Electrical Durability | 7000 cycle 60 cycles per hour |
| Mechanical Durability | 20000 cycle 120 cycles per hour |
| Number of Poles | 3P |
| Order Multiple | 1 piece |
| Rated Impulse Withstand Voltage (U _{imp}) | 8 kV |
| Rated Insulation Voltage (U _i) | 1000 V |
| Rated Operational Current AC-23A (I _e) | (400 V) 400 A (690 V) 400 A |
| Rated Operational Voltage | 690 V AC 750 V DC |
| Rated Short-time Withstand Current Low Voltage (I _{cw}) | 5 kA |
| Rated Uninterrupted Current (I _u) | 400 A |
| Standards | IEC60947-2 |
| Sub-type | XT5 |
| Terminal Connection Type | Front |

Certificates and Declarations

| | |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0206 1SDC210099D0206 |
| Declaration of Conformity - CE | 9AKK107680A2824 |
| Mechanical Drawings | 1SDH002011A1101 |

| | |
|--------------------------|-----------------|
| Wiring Diagram | 1SDM000005A1001 |
| Instructions and Manuals | 1SDH002011A1001 |

External Classifications and Standards

| | |
|----------------------------|--|
| ETIM 8 | EC000216 - Switch disconnecter |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| Object Classification Code | Q |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27371403 |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

