




---

 PRODUCT-DETAILS

## AF12-30-01-13

### AF12-30-01-13 100-250V50/60HZ-DC Contactor




---

**General Information**

Extended Product Type	AF12-30-01-13
Product ID	1SBL157001R1301
EAN	3471523110434
Catalog Description	AF12-30-01-13 100-250V50/60HZ-DC Contactor
Long Description	<p>The AF12-30-01-13 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 5.5 kW / 400 V AC (AC-3) or 7-1/2 hp / 480 V UL and switching power circuits up to 28 A (AC-1) or 28 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>

---

**Ordering**

Minimum Order Quantity	1 piece
------------------------	---------

### Popular Downloads

Data Sheet, Technical Information	1SBC100214C0202
Instructions and Manuals	1SBC101027M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

### Dimensions

Product Net Width	45 mm
Product Net Depth / Length	77 mm
Product Net Height	86 mm
Product Net Weight	0.27 kg

### Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Number of Poles	3P
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 28 A (690 V) 60 °C 28 A (690 V) 70 °C 24 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 60 °C 12 A (440 V) 60 °C 12 A (500 V) 60 °C 12.5 A (690 V) 60 °C 9 A (380 / 400 V) 60 °C 12 A (220 / 230 / 240 V) 60 °C 12 A
Rated Operational Current AC-3e (I <sub>e</sub> )	(415 V) 60 °C 12 A (440 V) 60 °C 12 A (500 V) 60 °C 12.5 A (690 V) 60 °C 9 A (380 / 400 V) 60 °C 12 A (220 / 230 / 240 V) 60 °C 12 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current DC-1 (I <sub>e</sub> )	(110 V) 1-Pole, 40 °C 15 A (110 V) 1-Pole, 60 °C 15 A

- (110 V) 1-Pole, 70 °C 15 A
- (110 V) 2 Poles in Series, 40 °C 27 A
- (110 V) 2 Poles in Series, 60 °C 27 A
- (110 V) 2 Poles in Series, 70 °C 24 A
- (110 V) 3 Poles in Series, 40 °C 27 A
- (110 V) 3 Poles in Series, 60 °C 27 A
- (110 V) 3 Poles in Series, 70 °C 24 A
- (220 V) 2 Poles in Series, 40 °C 15 A
- (220 V) 2 Poles in Series, 60 °C 15 A
- (220 V) 2 Poles in Series, 70 °C 15 A
- (220 V) 3 Poles in Series, 40 °C 27 A
- (220 V) 3 Poles in Series, 60 °C 27 A
- (220 V) 3 Poles in Series, 70 °C 24 A
- (72 V) 1-Pole, 40 °C 27 A
- (72 V) 1-Pole, 60 °C 27 A
- (72 V) 1-Pole, 70 °C 24 A
- (72 V) 2 Poles in Series, 40 °C 27 A
- (72 V) 2 Poles in Series, 60 °C 27 A
- (72 V) 2 Poles in Series, 70 °C 24 A
- (72 V) 3 Poles in Series, 40 °C 27 A
- (72 V) 3 Poles in Series, 60 °C 27 A
- (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational Current DC-3 (I<sub>e</sub>)

- (110 V) 1-Pole, 40 °C 7 A
- (110 V) 1-Pole, 60 °C 7 A
- (110 V) 1-Pole, 70 °C 7 A
- (110 V) 2 Poles in Series, 40 °C 27 A
- (110 V) 2 Poles in Series, 60 °C 27 A
- (110 V) 2 Poles in Series, 70 °C 24 A
- (110 V) 3 Poles in Series, 40 °C 27 A
- (110 V) 3 Poles in Series, 60 °C 27 A
- (110 V) 3 Poles in Series, 70 °C 24 A
- (220 V) 2 Poles in Series, 40 °C 7 A
- (220 V) 2 Poles in Series, 60 °C 7 A
- (220 V) 2 Poles in Series, 70 °C 7 A
- (220 V) 3 Poles in Series, 40 °C 27 A
- (220 V) 3 Poles in Series, 60 °C 27 A
- (220 V) 3 Poles in Series, 70 °C 24 A
- (72 V) 1-Pole, 40 °C 27 A
- (72 V) 1-Pole, 60 °C 27 A
- (72 V) 1-Pole, 70 °C 24 A
- (72 V) 2 Poles in Series, 40 °C 27 A
- (72 V) 2 Poles in Series, 60 °C 27 A
- (72 V) 2 Poles in Series, 70 °C 24 A
- (72 V) 3 Poles in Series, 40 °C 27 A
- (72 V) 3 Poles in Series, 60 °C 27 A
- (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational Current DC-5 (I<sub>e</sub>)

- (110 V) 1-Pole, 40 °C 4 A
- (110 V) 1-Pole, 60 °C 4 A
- (110 V) 1-Pole, 70 °C 4 A
- (110 V) 2 Poles in Series, 40 °C 15 A
- (110 V) 2 Poles in Series, 60 °C 15 A
- (110 V) 2 Poles in Series, 70 °C 15 A
- (110 V) 3 Poles in Series, 40 °C 27 A
- (110 V) 3 Poles in Series, 60 °C 27 A
- (110 V) 3 Poles in Series, 70 °C 24 A
- (220 V) 2 Poles in Series, 40 °C 4 A
- (220 V) 2 Poles in Series, 60 °C 4 A
- (220 V) 2 Poles in Series, 70 °C 4 A
- (220 V) 3 Poles in Series, 40 °C 12 A
- (220 V) 3 Poles in Series, 60 °C 12 A
- (220 V) 3 Poles in Series, 70 °C 12 A
- (72 V) 1-Pole, 40 °C 12 A
- (72 V) 1-Pole, 60 °C 12 A
- (72 V) 1-Pole, 70 °C 12 A
- (72 V) 2 Poles in Series, 40 °C 27 A
- (72 V) 2 Poles in Series, 60 °C 27 A
- (72 V) 2 Poles in Series, 70 °C 24 A
- (72 V) 3 Poles in Series, 40 °C 27 A
- (72 V) 3 Poles in Series, 60 °C 27 A
- (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational

(24 V) 6 A / 144 W

Current DC-13 ( $I_e$ )	(48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 ( $P_e$ )	(400 V) 5.5 kW (415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW
Rated Operational Power AC-3e ( $P_e$ )	(415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 106 A
Rated Insulation Voltage ( $U_i$ )	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	6 kV
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage ( $U_c$ )	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Power Loss	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 1 W at Rated Operating Conditions AC-3 per Pole 0.2 W
Operate Time	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 4 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 4 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 6 mm <sup>2</sup>
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup>

Connecting Capacity Control Circuit	Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Tightening Torque	Auxiliary Circuit 1.2 N-m Control Circuit 1.2 N-m Main Circuit 1.5 N-m
Terminal Type	Screw Terminals
Product Name	Block Contactor

### Technical UL/CSA

NEMA Size	0
Continuous Current Rating NEMA	18 A
Horsepower Rating NEMA	(115 V AC) Single Phase 1 Hp (200 V AC) Three Phase 3 Hp (230 V AC) Single Phase 2 Hp (230 V AC) Three Phase 3 Hp (460 V AC) Three Phase 5 Hp (575 V AC) Three Phase 5 Hp
Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 28 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 1 hp (200 ... 208 V AC) Three Phase 3 hp (220 ... 240 V AC) Three Phase 3 hp (240 V AC) Single Phase 2 hp (440 ... 480 V AC) Three Phase 7-1/2 hp (550 ... 600 V AC) Three Phase 10 hp
Connecting Capacity Main Circuit UL/CSA	Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 13 in-lb
Full Load Amps Motor Use	(120 V AC) Single Phase 16 A (200 ... 208 V AC) Three Phase 11 A (220 ... 240 V AC) Three Phase 9.6 A (240 V AC) Single Phase 12 A (440 ... 480 V AC) Three Phase 11 A (550 ... 600 V AC) Three Phase 11 A

### Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating	Without Derating 3000 m

Altitude Permissible

Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations	4g Closed Position & 2g Open position 5 ... 300 Hz
Pollution Degree	3

**Material Compliance**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	05ad0780-eb8f-4c45-a947-f9d3657697f2 China (CN)
Simplified SCIP	21f1d4f3-5fb9-4e3a-ab61-b02d26a92a30 Portugal (PT) 7b07a283-69de-4419-83f8-4e20d55aa52a Germany (DE) 48762244-41be-4960-a79d-6d9bbc2bce63 France (FR) a9b3aa08-5a22-4cba-9e4f-51ff5831c077 Germany (DE) 30669ee4-28f8-4eaa-ae79-f0da1fad4bcd Germany (DE) 8b90a69a-e4c3-4be7-9a6f-92207a33cd2f Poland (PL) fe4a9749-04b7-4dfa-a006-4de3751444cd Denmark (DK) ff87fca8-60ef-49d2-aeba-5ff46d271ba8 Sweden (SE) 5660fc72-758e-47e3-9fa3-d7451987a32b Belgium (BE) 52740d83-a031-43f8-9b9d-ba7a8c238e9c Estonia (EE) 04b3d1ce-4ce4-45b5-988f-54179741632e Hungary (HU) 2f27cad9-2cb3-4993-9357-6602963b0555 Hungary (HU) e8bdd1c0-bf9a-4581-b0a8-b81c7e344aa0 Netherlands (NL) ec1ee569-c3e8-4d69-ae67-3c78bb4ca808 Norway (NO) e79bd63d-3f12-4df5-85b6-ac664ec1ad07 Germany (DE) 2c6189a0-95e3-4a9b-94c4-0a420cd84a13 Croatia (HR) 10f034b5-69ab-4a9a-a85e-9788b6bb11ff Czech Republic (CZ) e389b6d5-0902-4896-b25a-8297e6690b23 Poland (PL) d74312c5-0377-487e-aa93-b1af16cd3502 Poland (PL) ddf0f29b-c9c5-4b88-a9fe-a646a6b161ed Finland (FI) 3dd36381-543e-4051-9262-9852fc3f2e54 Spain (ES) 4a6f5b39-9b4a-4100-9e7b-0c3559e301ff Bulgaria (BG) 7f35f44c-795e-4c4e-b8d5-31f8431feabc Greece (GR) 16391a2b-9c77-403b-a579-a9a012203b4e Belgium (BE) 65277a90-0956-43de-884a-ef12be5bb616 Sweden (SE) 8c5f9bc0-bb9f-4516-a11a-9ef7abe39ec4 Germany (DE) b2539be3-4f3f-4953-bd70-03be544e5183 France (FR)
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

**ABB EcoSolutions**

End Of Life Disassembling Instructions	1SBC101080M6801
Environmental Product Declaration - EPD	1SBD250584E3000 2TFP200035A1001
Sustainable Material Content in Packaging (wt. %)	Recycled Cardboard - 86 %
Sustainable Material Content in Product (wt. %)	Recycled Metal - 28 %

%)

**Certificates and Declarations**

A2L Certificate – UL	9AKK108469A4875 9AKK108469A4879
ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H24898CO
CB Certificate	CB_SE-113345
CCC Certificate	CCC_2010010304445624
CQC Certificate	CQC2010010304445624 CQC2020010304298240
Declaration of Conformity - CCC	2020980304001253 2020980304001082
Declaration of Conformity - CE	1SBD250000U1000
Declaration of Conformity - UKCA	1SBD250031U1000
DNV Certificate	DNV_TAE00001AF-4
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
KC Certificate	KC_HW02016-15005C
LR Certificate	LRS_LR23403517TA-02
RINA Certificate	RINA_ELE142224XG
RMRS Certificate	RMRS_1802705280
UL Certificate	UL-US-2150887-5 UL-CA-2142658-5
UL Listing Card	E312527

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	87 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.27 kg
Package Level 1 EAN	3471523110434
Package Level 2 Units	box 27 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	315 mm
Package Level 2 Gross Weight	7.29 kg
Package Level 3 Units	1296 piece

**External Classifications and Standards**

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003

UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> Iec Contactors
E-Number (Finland)	3706225
E-Number (Sweden)	3211365

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF12

