



PRODUCT-DETAILS

# BMFW425/AC30

## Residual Current Circuit Breaker



General Information	
Extended Product Type	BMFW425/AC30
Product ID	1SYF604062R1250
EAN	8906176431537
Catalog Description	Residual Current Circuit Breaker
Long Description	The RCCB BMFW425/AC30 assures protection to people and installations against fault current to earth. This product is manufactured according to IEC Standards for the markets where it is required.

Technical	
Rated Voltage (U <sub>r</sub> )	230/400 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Input Voltage Type	AC
Rated Current (I <sub>n</sub> )	25 A
Rated Frequency (f)	50 Hz
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle

Number of Poles	4P
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Flexible 35 mm <sup>2</sup> Flexible Solid;25 mm <sup>2</sup>

### Material Compliance

RoHS Status	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	Product Not in WEEE Scope

### Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20

### Dimensions

Product Net Width	70 mm
Product Net Height	88 mm
Product Net Depth / Length	74.25 mm
Product Net Weight	0.273 kg

### Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	304 g

### Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A0983
--------------------------------	-----------------

### Installation

Instructions and Manuals	9AKK108469A0989
--------------------------	-----------------

### Popular Downloads

Data Sheet, Technical Information	9AKK108469A4847
-----------------------------------	-----------------

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Formula Din Rail → Residual Current Circuit Breakers, Formula Din Rail

