




PRODUCT-DETAILS

XT5D 630 4p F F
XT5D 630 4p F F



General Information	
Extended Product Type	XT5D 630 4p F F
Product ID	1SDA100549R1
EAN	8056221006255
Catalog Description	XT5D 630 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX XT5D 630 FIXED FOUR-POLE WITH FRONT TERMINALS

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group	UL 2799 Zero Waste To Landfill Validation available
Waste To Landfill Target	
End Of Life Disassembling Instructions	9AKK108468A2353
Environmental Product Declaration - EPD	9AKK108468A9746 9AKK108468A1893
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 59.6 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	bf15f994-6831-4b5a-8a1d-08ff18684528 Italy (IT)
Simplified SCIP	b8ed9c1f-2415-4d42-9c32-b2becb3b5c0c Germany (DE) e13cdd0b-909b-4787-803c-fa77750dd19a Germany (DE) 953d7c07-5c4d-4af7-b279-138196e17b5f Poland (PL) 55687a76-c562-4e8d-bb42-49cdabe1199e Norway (NO) a18baa3c-7020-41d1-a72c-f13671d21b36 Finland (FI) 7d64434c-7722-4d62-9b3e-908ac2a7539f Netherlands (NL) c2697ba4-1c25-471f-b7d7-ae8731ad3c52 Germany (DE) b6a89e0f-1cd9-47f2-a01e-25e07a4425a5 Denmark (DK) 1fccba85-d044-47b0-b0b7-8b18bbc87015 Croatia (HR) d2dd09ce-cef0-4837-a976-65f4c6e6d872 Czech Republic (CZ) f18c772a-f5e2-418d-83a2-7fa4d57b9911 Poland (PL) fd2f2615-c0a9-4111-a6ba-3136479a3873 Netherlands (NL) cee2832c-72ff-4eef-9bec-22a52d64d496 Netherlands (NL) decfd2a6-3cd8-4eed-adbf-c16e9c9d2a44 Estonia (EE) 5f41e7ad-9a19-4e17-838e-cf2ec0222cd0 Portugal (PT) 34e7d555-b375-43e5-985d-51401b776d23 Bulgaria (BG) ed1e52be-0e22-4118-bafb-6e0aff8b39f6 Sweden (SE) 01c98c44-9950-4bb1-88c7-178a0e9a477d Poland (PL) d2748ad4-97e1-4430-88b1-6f3de75de0d1 France (FR) 33f5a350-2a8c-4ec2-b6ed-ee19926c271b Sweden (SE) 8e6ba879-e194-47fc-9cc0-45b3a7f732c4 Greece (GR) 0e971679-8bea-4de6-8b34-5905ab243498 Germany (DE) ee9a92f2-885e-452d-89a7-89a449ae9259 Germany (DE) ee806ff4-9fb6-4d27-8587-b4fd115b4aa8 France (FR) daadbc90-2a33-4be2-bd50-7736d56e4a5a Netherlands (NL) ac09edab-8219-472c-a9e4-e646b309df69 Spain (ES) b333577e-9c43-4856-bdb2-0470740cadb6 Netherlands (NL)

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT5DE4600DFF000XXX
E-Number (Norway)	4380447
EAN	8056221006255
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.6 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	248 mm

Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	6.088 kg
Package Level 1 EAN	8056221006255

Additional Information

Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Version	F
CAD Dimensional Drawing	1SDH002065A1183 1SDH002065A1131

Technical

Electrical Durability	5000 cycle 60 cycles per hour
Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4P
Order Multiple	1 piece
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-23A (I_e)	(400 V) 630 A (690 V) 630 A
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw})	7.6 kA
Rated Uninterrupted Current (I_u)	630 A
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

External Classifications and Standards

ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

