PRODUCT DATASHEET
SF CIRC 250 V 13W 830 IP44

SURFACE CIRCULAR 250 | Wall and ceiling luminaire with IP44



VALUE CLASS

Areas of application

- Corridors
- Stairways
- Bathrooms
- Foyers

Product benefits

- Indoor luminaire with high luminous efficacy
- Energy savings of up to 55 % compared to luminaires that use CFL
- Easy and quick installation
- Very homogenous light
- 3 years guarantee

Product features

- Type of protection: IP44 (ceiling mounting), IP20 (wall mounting)
- Impact resistance: IK03
- Metal housing, PMMA cover
- Ambient temperature in operation: -20…+40 °C
- Indoor use only, not suitable for outdoor use

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	13.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	100 mA
Inrush current	6.7 A
Inrush current time T_{h50}	228 µs
Max. number of luminaires per miniature circuit breaker B16	50
Max. number of luminaires per miniature circuit breaker C10	40
Max. number of luminaires per miniature circuit breaker C16	64
Power factor λ	> 0.55
Maximum total harmonic distortion	< 120 %
Protection class	I
Operating mode	Integrated LED driver


Photometrical data

Luminous flux	920 lm
Luminous efficacy	70 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Luminous intensity	-
Low flicker	Yes
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °
UGR	≤ 23

© 2026, LEDVANCE GmbH. All rights reserved.




SF CIRC 250 V 13W 830 IP44



SF CIRC 250 V 13W 830 IP44

Dimensions & Weight

Diameter	250.00 mm
Height	91.00 mm
Product weight	340.00 g



SF CIRCULAR 250

Materials & Colors

Product color	White
Housing color	White
Body material	Steel

© 2026, LEDVANCE GmbH. All rights reserved.

Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+80 °C
Type of connection	Terminal, 3-pin
Type of protection	IP44 [1)]
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	No

1) Type of protection: IP44 (ceiling mounting), IP20 (wall mounting)

Lifespan

Lifespan L70/B50 at 25 °C	30000 h [1)]
Lifespan L80/B10 at 25 °C	22000 h [1)]
Lifespan L80/B50 at 25 °C	22000 h
Lifespan L90/B10 at 25 °C	15000 h [1)]
Number of switching cycles	50000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	145 mA

Certificates & Standards

Standards	CE / CB / TÜV SÜD / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00010-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– Replacement cover optional available

© 2026, LEDVANCE GmbH. All rights reserved.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	SURFACE CIRCULAR SENSOR
PDF	Legal information	LS Insert SF Circular
PDF	Legal information	LS Insert SF Circular
PDF	Legal information	Legal insert
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11218810
PDF	Declarations of conformity	CE Declaration SF CIRC
PDF	Declarations of conformity UKCA	SF CIRC IP44
PDF	Declarations of conformity UKCA	SF CIRC
PDF	EPD	EPD EN SURFACE CIRCULAR SENSOR

	Photometric and lighting design files	Document name
IES	IES file (IES)	SF CIRC 250 V 13W 830 IP44
LDT	LDT file (Eulumdat)	SF CIRC 250 V 13W 830 IP44
ULD	ULD file (DIALux)	SF CIRC 250 V 13W 830 IP44
ROLF	ROLF file (RELUX)	SF CIRC 250 V 13W 830
	UGR file (UGR table)	SF CIRC 250 V 13W 830 IP44
	Light distribution curve type cone	SF CIRC 250 V 13W 830 IP44
	Light distribution curve type polar	SF CIRC 250 V 13W 830 IP44

	CAD/BIM files	Document name
RFA	BIM Revit 3D	SURFACE CIRCULAR

© 2026, LEDVANCE GmbH. All rights reserved.

	CAD/BIM files	Document name
	CAD STEP 3D	SF CIRC 250


	Tender texts	Document name
	Tender documents	SURFACE CIRCULAR 250 13W 830 IP44-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075617865	Folding box 1	280 mm x 282 mm x 98 mm	418.00 g	7.74 dm^3
4058075617872	Shipping box 5	510 mm x 292 mm x 305 mm	2688.00 g	45.42 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.