# PRODUCT DATASHEET
# Vintage 1906 PenduLum Bobbin Gun Metal

Vintage 1906 PenduLum Bobbin | Indoor pendant luminaires, vintage style, E27 socket



## Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)
- Professional (hotels, bars, boutiques etc.)

## Product benefits

- Individual light scenarios through combination with decorative lamp
- Glossy finish with great look and feel

## Product features

- Modern minimalistic design
- Made of classic materials
- Special vintage appeal when combined with 1906 lamps
- Flexible mounting options
- Available in various colors
- 1,5 m textile cable




© 2026, LEDVANCE GmbH. All rights reserved.

## TECHNICAL DATA

### Electrical data

| | |
|---|---|
| Nominal voltage | 220…240 V |
| Mains frequency | 50…60 Hz |
| Protection class | I |
| Operating mode | Mains voltage |

### Dimensions & Weight

| | |
|---|---|
| Diameter | 100.00 mm |
| Height | 1625.00 mm |
| Product weight | 298.00 g |
| Cable length | 1.5 m |




1906 PENDULUM BOBBIN
E27

### Materials & Colors

| | |
|---|---|
| Product color | Grey |
| Housing color | Grey |
| Body material | Steel |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

### Application & Mounting

| | |
|---|---|
| Ambient temperature range | -20…+40 °C |
| Temperature range at storage | -20…+80 °C |
| Type of connection | Screw terminal, 3-Pole |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Suspended |
| Application environment | Indoor |
| Mechanically adjustable | Yes |


© 2026, LEDVANCE GmbH. All rights reserved.

| | |
|---|---|
| With light source | No |
| Replaceable light source | Yes |
| Holder designation | E27 |

## Certificates & Standards

| | |
|---|---|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |

## Additional product data

| | |
|---|---|
| Product remark | Maximum bulb wattage: 25 W (LED 15 W) |
| Number of illuminants | 1 |

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

| | Documents and certificates | Document name |
|---|---|---|
| PDF | User instruction / safety instructions | VINTAGE 1906 PENDULUM |
| PDF | Legal information | Safety insert G11219601 |
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG |
| PDF | Declarations of conformity | CE Declaration 1906 |
| PDF | Declarations of conformity UKCA | PENDULUM |

## LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4099854419430 | Folding box<br>1 | 100 mm x 105 mm x 145 mm | 359.00 g | 1.52 $dm^3$ |
| 4099854419447 | Shipping box<br>4 | 230 mm x 220 mm x 170 mm | 1706.00 g | 8.60 $dm^3$ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.


© 2026, LEDVANCE GmbH. All rights reserved.

## References / Links

– Further information at www.ledvance.com/consumer/products/product-stories/vintage-edition-1906

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.


© 2026, LEDVANCE GmbH. All rights reserved.