PRODUCT DATASHEET
LS AY VAL -CSD/P4

CONNECTORS FOR RGB LED STRIP VALUE CLASS | Connectors for RGB LED Strips



VALUE CLASS

Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	3000 mA

Dimensions & Weight

Length	19.6 mm
Width	14.6 mm
Height	7.7 mm
Product weight	4.00 g

Colors & materials

Product color	Transparent/Black

Temperatures & operating conditions

Ambient temperature range	-15…+50 °C
Temperature range in operation	-15…+50 °C

Certificates & Standards

Type of protection	IP00

LOGISTICAL DATA

Temperature range at storage	-20…+85 °C

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	CE declaration LS AY VAL

	Tender texts	Document name
TXT	Tender documents	Connectors for RGB LED Strips CSDP4-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407831	BAG 2	80 mm x 120 mm x 5 mm	9.00 g	0.05 dm^3
4058075407848	Shipping box 100	120 mm x 100 mm x 120 mm	498.00 g	1.44 dm^3
4058075407855	Shipping box 1,000	525 mm x 140 mm x 270 mm	5371.00 g	19.85 dm^3

© 2026, LEDVANCE GmbH. All rights reserved.

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.