PRODUCT DATASHEET
TRUSYS FLEX P 35W 865 WW CL WT DALI

TRUSYS FLEX WALLWASHER | Luminaire inserts with asymmetric wallwasher light distribution, up to 175 lm/W



PERFOR-
MANCE
CLASS

Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, hardware stores
- Discounters, supermarkets

Product benefits

- Wall washer light distribution for directed wall illumination
- Easy installation, no tools required for connection
- Flexible application due to a range of different lumen packages and beam angles
- 5 years guarantee

Product features

- Beam angle wall washer: 1x40°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 175 lm/W
- Fixed luminare taps
- Luminaire versions available with on-off or IoT-ready DALI-2 driver
- Steel-sheet housing
- Lens material: PMMA
- Type of protection: IP40

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	35.00 W
Nominal voltage	220…240 V
Mains frequency	0/50/60 Hz
Nominal current	160.000 mA
Inrush current	22.4 A
Inrush current time T_{h50}	176 µs
Max. number of luminaires per miniature circuit breaker B16	18
Max. number of luminaires per miniature circuit breaker C10	15
Max. number of luminaires per miniature circuit breaker C16	25
Power factor λ	≥0.95
Maximum total harmonic distortion	≤ 15 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT

Photometrical data

Luminous flux	5700 lm
Luminous efficacy	165 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	3 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	40 °


© 2026, LEDVANCE GmbH. All rights reserved.



TRUSYS FLEX P 35W 865 WW CL WT DALI

Dimensions & Weight

Length	1500.00 mm
Width	77.70 mm
Height	39.40 mm
Product weight	1650.00 g



TRUSYS FLEX luminaire - clear

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9016
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)

© 2026, LEDVANCE GmbH. All rights reserved.

Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-25…+40 °C
Temperature range at storage	-40…+80 °C
Type of connection	Plug-In connection
Type of protection	IP40
Protection class IK (shock resistance)	IK04
Dimmable	Yes
Type of dimming	DALI
IoT ready	Support of DALI data type PART 251, 252, 253 [1)]
Mounting type	Suspended/Surface
Mounting location	Mounting rail
Application environment	Indoor
Mechanically adjustable	No
With light source	Yes
Replaceable light source	No

1) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h [1)]
Lifespan L80/B10 at 25 °C	76000 h [1)]
Lifespan L80/B50 at 25 °C	89000 h
Lifespan L90/B10 at 25 °C	43000 h [1)]
Number of switching cycles	100000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	400 mA
Output ripple current (100 Hz)	< 10 %

Emergency lighting

Type of Emergency Lighting (EL)	EL certified driver (0Hz / DC operation) for central battery operation included
Type of emergency operation test	None

© 2026, LEDVANCE GmbH. All rights reserved.

Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	VIVARES

Components for light control

Components Light Control

Product image	Product name	EAN
	MANUAL CONTROL UNIT GROUP DALI-2 TW	4099854748691
	MANUAL CONTROL UNIT SELECT DALI-2	4058075837485
	MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508
	MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522
	MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560
	MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546
	PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075837584

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	PUSH CONTROL UNIT FM DALI-2 DIM	4099854846922
	SURFACE MOUNT FRAME	4058075843561
	PUSHBUTTON COUPLER DALI-2	4058075837607
	FLEX CONTROL UNIT IOT DALI-2 HCL TW	4058075841888
	FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901
	FLEX CONTROL UNIT DALI-2 TW	4058075843844
	FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925
	SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621
	SENSOR CEILING MOUNTING KIT LIGHT/PRESENCE-6	4099854748714
	SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949
	SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882
	HIGHBAY SENSOR DALI-2 LIGHT/PRESENCE -21 INFRARED CEILING MOUNTING	4058075857537
	DALI sensors -8 IR CI, -40X5 IR CI, -24 IR CM, -21 IR CM	4058075843905
	RELAY DALI-2 RAIL MOUNTING	4099854709159
	RELAY DALI-2 CEILING MOUNTING	4099854709135
	REPEATER DALI-2 RAIL MOUNTING	4099854709111
	REPEATER DALI-2 CEILING MOUNTING	4099854709098

EQUIPMENT / ACCESSORIES

– Mounting rail with fixed integrated 5- and 8-pole cable

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	TRUSYS FLEX DALI 865
PDF	Legal information	Legal insert TRUSYS FLEX DALI
PDF	Legal information	LSI TRUSYS FLEX 865 DALI
PDF	Legal information	Informationstext 18 Abs 4 ElektroG

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	Declarations of conformity	TRUSYS FLEX DALI
PDF	Declarations of conformity UKCA	TRUSYS FLEX DALI
PDF	Certificates	ENEC Certificate Trusys Flex DALI
PDF	EU Data Act	DALI LED Driver and Luminaires

	Photometric and lighting design files	Document name
IES	IES file (IES)	TRUSYS FLEX P 35W 865 WW CL WT DALI
LDT	LDT file (Eulumdat)	TRUSYS FLEX P 35W 865 WW CL WT DALI
ULD	ULD file (DIALux)	TRUSYS FLEX P 35W 865 WW CL WT DALI
ROLF	ROLF file (RELUX)	TRUSYS FLEX P 35W 865 WW CL WT DALI
	Light distribution curve type polar	TRUSYS FLEX P 35W 865 WW CL WT DALI

	CAD/BIM files	Document name
RFA	BIM Revit 3D	TRUSYS FLEX
STEP	CAD STEP 3D	TruSys FLEX

	Tender texts	Document name
TXT	Tender documents	TRUSYS FLEX WALLWASHER 35W 865 WW CL WT DALI-EN


LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854191152	Folding box 1	108 mm x 1,534 mm x 102 mm	1825.00 g	16.90 dm^3
4099854191169	Shipping box 4	1,547 mm x 218 mm x 231 mm	8093.00 g	77.90 dm^3


The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.


© 2026, LEDVANCE GmbH. All rights reserved.


ADDITIONAL CATALOG INFORMATION














References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.