

Kanlux



EAN: 5905339384201

LED floodlight
Kanlux 38420 FL AGOR PRO 100W NW



IP
65



Date of issue: 24.04.2026, 11:05

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN

PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Maximum power [W]	100
Power factor	0.99
Luminous flux [lm]	14000
Correlated colour temperature [K]	4000
Colour consistency in McAdam ellipses	≤6
Colour temperature	white
Luminous efficiency of the lamp [lm/W]	140
Lighting angle [°]	110
Diode type	LED SMD
Integrated LED light source	yes
Colour rendering index	80
Service life [h]	50000
Number of on/off cycles	≥25000
Place of application	for industrial applications
IP class	65
IK class	08
Place of application	for industrial applications
Compatible with a dimmer	no
Wire type	H05RN-F
Wire diameter [mm²]	1
The fixture is movable vertically [°]	180
LED light source replaceability	It is not possible to replace the LED light source
Control gear replaceability	It is not possible to replace the control panel or control equipment
Product category according to 2019/2020/EU	Containing product (CP)
Mercury content	no
Mercury content in the lamp [mg]	0

DIMENSIONS AND MOUNTING

Height [mm]	253
Width [mm]	291
Depth [mm]	78
Wire length [m]	0.28
Place of assembly	wall mounted, ceiling mounted, surface mounted
Connection type	Free cable ends

LIGHT SOURCE PARAMETERS

LED module	FL71A-100C 48S3P
Energy efficiency class of the light source in the contains product (CP)	D
Number of modules (LED light source)	1

SENSOR PARAMETERS

Wykrywanie ruchu	no
------------------	----

MATERIAL AND CONSTRUCTION

Colour	black
Enclosure material	Metal
Lampshade material	Tempered glass
Reflector type	symmetrical
Class of protection against electric shock	I
Minimum distance from the illuminated object	1m
Ambient temperature range to which the product can be exposed	-30÷45

LOGISTICS

Unit of measurement	unit
Packaging method	4
Number of units in the secondary packaging	1

Date of issue: 24.04.2026, 11:05

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

LIGHT SOURCE PARAMETERS

Useful luminous flux of the light source Φ_{use} [lm]	16900
Useful luminous flux of the light source Φ_{use} [lm]	in sphere (360°)
Standby power (Psb)	0
Height of the light source [mm]	110
Width of the light source [mm]	190
Depth of the light source [mm]	2
Chromaticity coordinates (x)	0,38
Chromaticity coordinates (y)	0,38
Claim of equivalent power [W]	872
R9 colour rendering index value	0
Survival factor	0,9
The lumen maintenance factor	0.96
LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	Not applicable
Colour-tuneable light source	no
High luminance light source	no
Anti-glare shield	no
Dimmable	no


LOGISTICS

Number of units in the packaging	4
Net unit weight [g]	1940
Grammage [g]	2285
Gross unit weight [g]	2178
Length of a unit pack [cm]	31
Width of a unit pack [cm]	5.5
Height of a unit pack [cm]	28.5
Weight of a cardboard box [kg]	9.14
Width of a cardboard box [cm]	25.5
Height of a cardboard box [cm]	31
Length of a cardboard box [cm]	32
Volume of a cardboard box [m ³]	0.025296

ADDITIONAL INFORMATION


5 years Warranty under the terms of the warranty statement, available on our website

PHOTOMETRIC DATA



KANLUX S.A. (kat 38420) FL AGOR PRO 100W NW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 38420) FL AGOR PRO 100WNW
Lampy: 1 x FL AGOR PRO 100W



Date of issue: 24.04.2026, 11:05

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com