PRODUCT DATASHEET
SP ADJ P 8W 930 PS DIM IP20 WT

SPOT ADJUST | Recessed mounted spotlight for indoor use, adjustable



Areas of application

- Direct replacement for recessed spotlights with halogen lamps
- General illumination
- Hotel rooms and corridors
- Bars, restaurants
- Accent lighting
- Galleries, museums
- Residential interiors

Product benefits

- Energy savings of up to 90 % compared to halogen lamp spotlights
- Multi Lumen: Brightness adjustment via dip switches on the driver
- Easy replacement of external driver thanks to plug with bayonet lock
- Easy installation and electrical connection thanks to tool-free electrical connectors
- SCALE Design – great appearance, valuable materials and small size fits into every surrounding

Product features

- Available for ceiling cut-out diameters of 68 mm and 83 mm
- Adjustable swivel angle: ±25°
- Color rendering index R_a: 90
- Beam angle: 36°
- Die-cast aluminum housing
- Silicon-pad protected springs
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Through-wiring possible



© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	8 W / 6 W / 4 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	37mA / 28mA / 20 mA
Inrush current	2 A
Inrush current time T_{h50}	60 µs
Max. number of luminaires per miniature circuit breaker B16	336
Max. number of luminaires per miniature circuit breaker C10	210
Max. number of luminaires per miniature circuit breaker C16	336
Power factor λ	0.90
Maximum total harmonic distortion	< 20 %
Protection class	II
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	1 kV
Operating mode	Electronic control gear (ECG)
Dimming interface	Phase Cut


Photometrical data

Luminous flux	680 lm / 510 lm / 340 lm
Total luminous flux of contained light sources	620 lm
Luminous efficacy	85 lm/W
Color temperature	3000 K
Reference control setting of contained light source (Kelvin)	3000 K
Light color (designation)	Warm White
Color rendering index Ra	90
Standard deviation of color matching	≤3 sdcm
Luminous intensity	1200 cd
Low flicker	Yes
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	36 °
UGR	< 28

© 2026, LEDVANCE GmbH. All rights reserved.




SP ADJ P 8W 930 PS DIM IP20 WT



SP ADJ P 8W 930 PS DIM IP20 WT

Dimensions & Weight

Diameter	81.00 mm
Height	43.00 mm
Product weight	220.00 g



SP ADJ P 8W PS DIM IP20

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9016
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA

© 2026, LEDVANCE GmbH. All rights reserved.

Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+80 °C
Type of connection	Push terminal
Type of protection	IP20/IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	68 mm
Mounting depth	50,0 mm
Mechanically adjustable	Yes
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h [1)]
Lifespan L80/B10 at 25 °C	41000 h [1)]
Lifespan L80/B50 at 25 °C	41000 h
Lifespan L90/B10 at 25 °C	18000 h [1)]
Number of switching cycles	30000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	180 mA
Output ripple current (100 Hz)	< 10 %
ECG - Length	68.00 mm
ECG - Width	55,0 mm
ECG - Height	22.00 mm

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD

© 2026, LEDVANCE GmbH. All rights reserved.

Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00014-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	MULTI LUMEN

Accessories Optional

Product image	Product name	EAN
	SPOT FRAME 100X200 2X D68 BK	4099854460081
	SPOT FRAME 100X200 2X D68 WT	4099854460029
	SPOT FRAME 100X300 3X D68 WT	4099854460203
	SPOT FRAME 100X200 2X D68 SI	4099854460111
	SPOT FRAME 100X300 3X D68 BK	4099854460258
	SPOT FRAME 100X100 1X D68 SI	4099854459962
	SPOT FRAME 100X300 3X D68 SI	4099854460289
	SPOT FRAME 100X100 1X D68 WT	4099854459863

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	SPOT FRAME 100X100 1X D68 BK	4099854459917
	SP RING D100 BK	4099854136542
	SP RING D100 WT	4099854136511
	SP DRIVER DALI 8W	4099854089558
	SP RING D180 WT	4099854013416
	CONNECTOR BOX 3POLE L/N/E	4099854013508
	SP HOLDER DN68 H65	4099854013478
	SP RING D180 BK	4099854013447
	SP RING D133 BK	4099854013386
	SP RING D133 WT	4099854013355

Components for light control

Components Light Control

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	MANUAL CONTROL UNIT SELECT DIM	4099854846724
	MANUAL CONTROL UNIT SELECT DIM EXCHANGEABLE	4099854846823
	PUSH CONTROL UNIT FM DALI-2 DIM	4099854846922

EQUIPMENT / ACCESSORIES

- External control gear included with dip-switches to select power during installation
- Refurbishment rings are available as accessory
- Selected DALI 2.0 driver available as accessory

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI SP FIX P and SP FIX ADJ
PDF	Addon technical information	Dimmerlist SPOT GEN2
PDF	Legal information	Light source Insert SP FIX P PS DIM IP44
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Legal Insert G11147511
PDF	Legal information	Safety Insert G11262697
PDF	Declarations of conformity	CE Declaration of Conformity SPOT DIM
PDF	Declarations of conformity UKCA	UKCA Declaration of Conformity SPOT DIM

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	Declarations of conformity UKCA	SP DIM
PDF	Certificates	SP GEN2
PDF	EPD	EPD EN SPOTLIGHT ADJUST GEN 2

	Photometric and lighting design files	Document name
IES	IES file (IES)	SP ADJ P 8W 930 PS DIM IP20 WT
LDT	LDT file (Eulumdat)	SP ADJ P 8W 930 PS DIM IP20 WT
ULD	ULD file (DIALux)	SP ADJ P 8W 930 PS DIM
ROLF	ROLF file (RELUX)	SP ADJ P 8W 930 PS DIM
	UGR file (UGR table)	SP ADJ P 8W 930 PS DIM IP20 WT
	Light distribution curve type cone	SP ADJ P 8W 930 PS DIM IP20 WT
	Light distribution curve type polar	SP ADJ P 8W 930 PS DIM IP20 WT

	CAD/BIM files	Document name
RFA	BIM Revit 3D	SP ADJ G2
STEP	CAD STEP 3D	SP ADJ

	Tender texts	Document name
TXT	Tender documents	SPOT ADJUST 8W 930 PS DIM IP20 WT-EN


LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075799646	Folding box 1	100 mm x 105 mm x 85 mm	264.00 g	0.89 dm^3
4058075799653	Shipping box 20	562 mm x 230 mm x 195 mm	5630.00 g	25.21 dm^3

© 2026, LEDVANCE GmbH. All rights reserved.

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION





References / Links

- For Guarantee see www.ledvance.com/guarantee
- Discover our matching phase-cut dimmers www.ledvance.com/phase-cut-dimmers
- For dimming conformity see www.ledvance.com/dim

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.