PRODUCT DATASHEET
LN COMP SWITCH 600 8 W 4000 K

LINEAR COMPACT SWITCH | Compact single or light line luminaire with switch



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Accent lighting
- Public areas
- Cove lighting
- Shelves, furniture integration or under cabinet mounting
- Seamless linear lighting

VALUE CLASS

Product benefits

- Compact dimensions
- Little space required thanks to compact dimensions
- Seamless connection of up to 10 luminaires in a line
- Handy switch directly installed on the luminaire
- Low flicker light thanks to special electronic control gear
- Flexible installation in 2 different angles with 2 different mounting options
- Flexible application due to a wide range of available lengths of 300 to 1500 mm.
- Angled connection possible with included cable

Product features

- Built-in switch
- Up to 10 luminaires connectable
- Translucent end caps
- Versions with luminous flux 400…1900 lm available

© 2026, LEDVANCE GmbH. All rights reserved.

- 5 different lengths available
- Luminous efficacy: up to 112 lm/W
- Glow Wire Test according to IEC 60695-2-12: 850 °C

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	8.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	0.06 A
Inrush current	10,0 A
Inrush current time T_{h50}	150 µs
Max. number of luminaires per miniature circuit breaker B16	60
Max. number of luminaires per miniature circuit breaker C10	48
Max. number of luminaires per miniature circuit breaker C16	76
Power factor λ	> 0.5
Maximum total harmonic distortion	89 %
Protection class	II
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	800 lm
Luminous efficacy	100 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG0
Beam angle	140 °


© 2026, LEDVANCE GmbH. All rights reserved.



LN COMP SWITCH 600 8W 4000K 230V IP20

Dimensions & Weight

Length	573.00 mm
Width	28.00 mm
Height	36.00 mm
Product weight	300.00 g



LN COMP SWITCH 600

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9016
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

© 2026, LEDVANCE GmbH. All rights reserved.

Application & Mounting

Ambient temperature range	-20…+40 °C
Type of connection	Power cable/Plug
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h [1)]
Lifespan L80/B10 at 25 °C	40000 h [1)]
Lifespan L80/B50 at 25 °C	40000 h
Lifespan L90/B10 at 25 °C	30000 h [1)]
Number of switching cycles	100000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	100 mA

Certificates & Standards

Standards	CE / CB / TÜV SÜD / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00018-V01.01-EN

EQUIPMENT / ACCESSORIES

- Equipped with power plug, cable connector and line adapter for connecting further luminaires
- Mounting material for wall and ceiling installations included

Safety advice

- All electrical connections must be made by a qualified person.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm’s reach.

© 2026, LEDVANCE GmbH. All rights reserved.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Linear_Compact_Switch_UI
PDF	On-Pack-Info	Legal Insert Linear Compact
PDF	Legal information	LS Insert LN COMP HO and SWITCH
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11218810
PDF	Legal information	Legal Insert G11231524
PDF	Declarations of conformity	EU Declaration of Conformity Linear Comp Switch and HO LEDV
PDF	Declarations of conformity	Attestation of Conformity Linear Comp
PDF	Declarations of conformity UKCA	LN COMP SWITCH
PDF	EPD	EPD EN LINEAR COMPACT SWITCH

	Photometric and lighting design files	Document name
IES	IES file (IES)	LN COMP SWITCH 600 8W 4000K 230V IP20
LDT	LDT file (Eulumdat)	LN COMP SWITCH 600 8W 4000K 230V IP20
ULD	ULD file (DIALux)	LINEARCOMPACTSWITCH6008W4000K
ROLF	ROLF file (RELUX)	LN COMP SWITCH 600
	UGR file (UGR table)	LN COMP SWITCH 600 8W 4000K 230V IP20
	Light distribution curve type polar	LN COMP SWITCH 600 8W 4000K 230V IP20

	CAD/BIM files	Document name
RFA	BIM Revit 3D	Linear Compact

© 2026, LEDVANCE GmbH. All rights reserved.

	CAD/BIM files	Document name
	CAD STEP 3D	LN COMP SWITCH 600


	Tender texts	Document name
	Tender documents	LINEAR COMPACT SWITCH 600 8 W 4000 K-EN


LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075106130	Folding box 1	780 mm x 40 mm x 30 mm	364.00 g	0.94 dm^3
4058075106147	Shipping box 25	818 mm x 223 mm x 180 mm	8020.00 g	32.83 dm^3


The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION









References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.