PRODUCT DATASHEET
PL CMFT 1200 P 33W 840 PS

PANEL COMFORT 1200 PS | Rectangular recessed panel luminaires with Multi Lumen function, for 1200 x 300 mm ceiling systems

Areas of application

- Direct replacement for recessed luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators
- Suitable for recessed ceiling systems with grid size of 1200 x 300 mm

Product benefits

- Highly versatile due to selectable lumen steps (Multi Lumen) on the driver
- Tool-free electrical connection due to push button connector
- Through-wiring possible with included connector box
- High color consistency with SDCM 3
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- External driver for extended flexibility and easy installation
- Low flicker light thanks to special electronic control gear
- Emergency lighting possible with LEDVANCE Emergency Conversion Box
- 5 years guarantee

Product features

- Extruded aluminum frame
- Polystyrene diffuser
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm^2
- Luminaire versions with IoT-ready DALI-2 driver available
- Lifetime (L80/B10): 70,000 h (at 25 °C)

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	33 W / 28 W / 24 W [1)]
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	150.000 mA
Inrush current	9 A
Inrush current time T_{h50}	690 µs
Max. number of luminaires per miniature circuit breaker B16	14
Max. number of luminaires per miniature circuit breaker C10	15
Max. number of luminaires per miniature circuit breaker C16	24
Power factor λ	> 0.90
Maximum total harmonic distortion	< 20 %
Protection class	II
Operating mode	External LED driver


1) For possible options refer to lumen/power table image / CRI80 versions of the Panel Comfort family are fulfilling the technical minimum requirements according to the German BEG subsidy program for energy efficient luminaires

Photometrical data


Luminous flux	4320 lm / 3640 lm / 3120 lm [1)]
Luminous efficacy	130 lm/W [1)]
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤3 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	110 °
CIE Flux code	47 79 96 100 100

1) For possible options refer to lumen/power table image / CRI80 versions of the Panel Comfort family are fulfilling the technical minimum requirements according to the German BEG subsidy program for energy efficient luminaires


© 2026, LEDVANCE GmbH. All rights reserved.




PL CMFT 1200 33W 840 PS EM CONVERSION BOX



PL CMFT 1200 33W 840 PS




PL CMFT 1200 33W 840 PS EM CONVERSION BOX



PL CMFT 1200 33W 840 PS

Dimensions & Weight

Length	1195.00 mm
Width	295.00 mm
Height	11.00 mm
Product weight	2800.00 g



PL COMP 1200

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003

© 2026, LEDVANCE GmbH. All rights reserved.

Body material	Steel
Cover material	Polystyrene (PS)
Light emitting surface material	Polystyrene
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10…+50 °C
Temperature range at storage	-20…+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP40/IP20
Protection class IK (shock resistance)	IK02
Dimmable	No
Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting length	1185 mm
Mounting width	285 mm
Mounting depth	50,0 mm
Mechanically adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h [1)]
Lifespan L80/B10 at 25 °C	70000 h [1)]
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	48000 h [1)]
Number of switching cycles	50000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	750 mA
Output ripple current (100 Hz)	< 5 %
ECG - Length	143 mm
ECG - Width	49 mm
ECG - Height	30 mm

© 2026, LEDVANCE GmbH. All rights reserved.

Recommended control gear	OSRAM OTI DALI 50/220-240/1A4 NFC; Tridonic LCA 45W 500-1400mA one4all SC PRE

Emergency lighting

Type of Emergency Lighting (EL)	Optional EL unit (battery and controller) for decentral operation available separately

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00012-V01.01-EN

Additional product data

Added function	MULTI LUMEN

Accessories Optional

Product image	Product name	EAN
	PANEL 1200 CABLE EXT TWIST LOCK	4099854018510
	EM CONVERSION BOX	4058075237025
	PANEL 1200x300 RECESSED MOUNT FRAME	4058075472976
	PANEL 1200 Surface Mount Kit	4058075108820
	PANEL RECESSED MOUNT CLIPS VAL 4x	4058075409859

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	PANEL Suspension Kit	4058075402928
	PANEL 1200 X 300 SF MOUNT KIT H70 VAL	4099854018497

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- Connector box with 5-pole terminal included
- Security rope for luminaire included
- Security brackets preinstalled
- External control gear included
- Separate DC twist lock cable extension available
- Suitable for use with separate Emergency Conversion Box

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	PL CMFT 1200 P
PDF	Legal information	LISO Insert Panel CMFT 1200 P
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	EM Insert PL COMFORT
PDF	Declarations of conformity	CE Declaration PL CMFT 1200 PS
PDF	Declarations of conformity UKCA	UKCA Declaration PL CMFT PS
PDF	Declarations of conformity UKCA	PL CMFT PS

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	EPD	EPD EN PANEL COMFORT EDGELIT DALI

	Photometric and lighting design files	Document name
IES	IES file (IES)	PL CMFT 1200 33W 840 PS
LDT	LDT file (Eulumdat)	PL CMFT 1200 33W 840 PS
ULD	ULD file (DIALux)	PL CMFT 1200 P 33W 840 PS
ROLF	ROLF file (RELUX)	PL CMFT 1200 P 33W 840 PS
	UGR file (UGR table)	PL CMFT 1200 33W 840 PS EM CONVERSION BOX
	UGR file (UGR table)	PL CMFT 1200 33W 840 PS
	Light distribution curve type cone	PL CMFT 1200 33W 840 PS EM CONVERSION BOX
	Light distribution curve type cone	PL CMFT 1200 33W 840 PS
	Light distribution curve type polar	PL CMFT 1200 33W 840 PS EM CONVERSION BOX
	Light distribution curve type polar	PL CMFT 1200 33W 840 PS

	CAD/BIM files	Document name
RFA	BIM Revit 3D	PL_CMFT
STEP	CAD STEP 3D	PL_CMFT_1200

	Tender texts	Document name
TXT	Tender documents	PANEL COMFORT 1200 PS 33W 840 PS-EN

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854003981	Folding box 1	37 mm x 344 mm x 1,347 mm	3252.00 g	17.14 dm^3


© 2026, LEDVANCE GmbH. All rights reserved.


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854003998	Shipping box 4	1,377 mm x 167 mm x 379 mm	13420.00 g	87.15 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION







References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.