



PRODUCT DATASHEET

DULUX LED S/E11 AC MAINS VALUE 6W 830 2G7

DULUX LED S/E AC MAINS VALUE | LED replacement for CFLni with 4-pin 2G7 base for AC mains operation



Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Offices, public buildings
- Shops
- Hotels, restaurants
- Walkways and corridors

Product benefits

- Operation directly on 230 V AC mains
- Not suitable for operation with conventional control gear (CCG)
- Not suitable for operation with electronic control gear (ECG)
- Easy installation
- Easy relamping thanks to compact design

Product features

- LED replacement for conventional compact fluorescent lamps for use on AC mains
- Lifetime up to 30,000 h
- Single-ended four-pin plug-in 2G7 base
- Type of protection: IP20



TECHNICAL DATA


Electrical data

Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	220...240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	11 W
Nominal current	28 mA
Type of current	AC
Inrush current	19.6 A
Suitable for DC input	Yes
Input voltage DC	186...270 V ¹⁾
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	30
Max. lamp number on MCB B16 A	38
Total harmonic distortion	≤ 20 %
Power factor λ	> 0.90

1) Permitted voltage range

Photometrical data

Luminous flux	700 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	80
Light color	830
Standard deviation of color matching	≤6 sdcn
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4




EPREL data spectral
diagram PROF LEDr 3000K

Light technical data

Beam angle	130 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	220.00 mm
Product weight	50.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C ¹⁾
Maximum temperature at tc test point	86 °C

1) Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.96
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	2G7
-----------------------------	-----

Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	E ¹⁾
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	DULUX LED S/E11
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	2G7
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	No
Length	220.00 mm
Height	20.8 mm
Width	32 mm

Chromaticity coordinate x	0.434
Chromaticity coordinate y	0.403
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	2416879
Model number	AC85415

Safety advice

- Not suitable for operation with conventional control gear.
- Not suitable for operation with electronic control gear.
- The operating temperature range of DULUX LED is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Lamp not suitable for emergency operation.
- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	DULUX LED SE
	Extended installation guide	LEDVANCE Luminaire conversion checklist
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	CE DULUX LED SE
	Declarations of conformity UKCA	UKCA DULUX LED SE
	Certificates	DULUX LED SE11 AC V 6W
	Certificates	DULUX LED SE11 AC V 6W
	Certificates	DULUX LED SE11 AC V 6W

Photometric and lighting design files		Document name
	IES file (IES)	DULUX LED S E11 AC V 6W 830 2G7 LEDV
	LDT file (Eulumdat)	DULUX LED S E11 AC V 6W 830 2G7 LEDV
	UGR file (UGR table)	DULUX LED S E11 AC V 6W 830 2G7 LEDV
	Light distribution curve type cone	DULUX LED S E11 AC V 6W 830 2G7 LEDV
	Light distribution curve type polar	DULUX LED S E11 AC V 6W 830 2G7 LEDV
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 3000K

Tender texts	Document name
 Tender documents	DULUX LED S E AC MAINS VALUE 6W 830 2G7-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854669750	Folding box 1	24 mm x 40 mm x 225 mm	64.00 g	0.22 dm ³
4099854669767	Shipping box 10	131 mm x 89 mm x 239 mm	727.00 g	2.79 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.