PRODUCT DATASHEET
LN INV D 1200 P 40W 930 PS ASY WT

LINEAR INDIVILED DIRECT 1200 PS ASYMMETRIC | Surface mounted luminaire for single or light line office application with CRI90, Multi Lumen function and asymmetric light distribution, 1200 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- High performance with CRI90 and up to 115 lm/W
- Highly versatile due to selectable lumen steps (Multi Lumen) on the driver
- Asymmetric light distribution for various application areas
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color
- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separetely)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm^2
- Lifetime (L80/B10): 70,000 h (at 25 °C)

© 2026, LEDVANCE GmbH. All rights reserved.

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	40 W / 35 W / 30 W / 25 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	180mA / 165mA / 135mA / 115 mA
Inrush current	15 A
Inrush current time T_{h50}	50 µs
Max. number of luminaires per miniature circuit breaker B16	50
Max. number of luminaires per miniature circuit breaker C10	36
Max. number of luminaires per miniature circuit breaker C16	58
Power factor λ	> 0.90
Maximum total harmonic distortion	≤ 20 %
Protection class	I
Surge capability (L-N)	1000 V
Surge capability (L/N-Ground)	2000 V
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	4350 lm / 3900 lm / 3400 lm / 2850 lm
Luminous efficacy	109 lm/W / 111 lm/W / 113 lm/W / 114 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥90
Standard deviation of color matching	3 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	55 ° x 55 °
UGR	< 19

© 2026, LEDVANCE GmbH. All rights reserved.




LN INV D 1200 P 40W 930 PS ASY WT 800mA

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
40 W	3000 K	4350 lm	109 lm/W
35 W	3000 K	3900 lm	111 lm/W
30 W	3000 K	3400 lm	113 lm/W
25 W	3000 K	2850 lm	114 lm/W

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3200.00 g



LN INV 1200 P

© 2026, LEDVANCE GmbH. All rights reserved.

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+50 °C
Temperature range at storage	-20…+80 °C
Type of connection	Screwless terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mechanically adjustable	No
With light source	Yes
Replaceable light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h [1)]
Lifespan L80/B10 at 25 °C	70000 h [1)]
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h [1)]
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	800mA / 700mA / 600mA / 500 mA
Output ripple current (100 Hz)	≤ 5 %
Recommended control gear	OSRAM IT FIT 40/220-240/800 CS L

© 2026, LEDVANCE GmbH. All rights reserved.

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00027-V01.01-EN
Replaceable light source (EPREL)	Only by an expert

Additional product data

Number of illuminants	1
Added function	EVERLOOP / MULTI LUMEN

Accessories Optional

Product image	Product name	EAN
	LN INV SUSPENSION KIT WT	4099854215537
	LN INV SUSPENSION WIRE	4099854323980
	LN INV 1200 THROUGHWIRING KIT	4099854214820
	LN INV INLINE CONNECTOR	4099854215612
	LN INV CORNER CONNECTOR WT	4099854308093
	LN INV INFILL 600 WT	4099854214882
	LN INV INFILL 1200 WT	4099854214868

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	LN INV INFILL 1500 WT	4099854214844

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Upgrade and replacement components

Components Light Source

Product image	Product name	EAN
	LISOEV 1074x29 43 40W 930 A55x55 GY	4099854652172

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	LN INV
PDF	Addon technical information	LN INV D PS ASY
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11205497
PDF	Legal information	Legal Insert G11235609
PDF	Declarations of conformity	LN INV

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	Declarations of conformity UKCA	LN INV
PDF	EPD	EPD EN LINEAR INDIVILED DIRECT DALI

	Photometric and lighting design files	Document name
IES	IES file (IES)	LN INV D 1200 P 40W 930 PS ASY WT 800mA
LDT	LDT file (Eulumdat)	LN INV D 1200 P 40W 930 PS ASY WT 800mA
	Light distribution curve type polar	LN INV D 1200 P 40W 930 PS ASY WT 800mA

	CAD/BIM files	Document name
STEP	CAD STEP 3D	LN INV D 1200 G2


	Tender texts	Document name
TXT	Tender documents	LINEAR INDIVILED DIRECT 1200 PS ASYMMETRIC 1200 P 40W 930 PS ASY WT-en


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854135392	Folding box 1	178 mm x 1,263 mm x 103 mm	3800.00 g	23.16 dm^3
4099854135408	Shipping box 2	1,277 mm x 187 mm x 189 mm	9000.00 g	45.13 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION





References / Links

– For Guarantee see www.ledvance.com/guarantee

© 2026, LEDVANCE GmbH. All rights reserved.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.