
PRODUCT DATASHEET
FL MAX PSU DA P 1200W WAL

FLOODLIGHT MAX POWER SUPPLY | Driver boxes for luminaire power, ensuring optimal connectivity via On/Off, DALI, DMX



PERFOR-
MANCE
CLASS

Areas of application

- Suitable for indoor and outdoor installations
- Ports/logistics: lights deep & wide areas, ideal with C5 corrosion protection

Product benefits

- For extreme temperatures: –40 °C to +50 °C (outdoors), up to +40 °C (indoors)
- Driver box installable up to 150 m from head, central maintenance, reduced mast weight
- Pre-fitted connectors enable quick, waterproof wiring on site (IP66)
- Standardized drivers are always easy to replace for simple maintenance
- Auxiliary DALI power for sensor and control integration, e.g. Smart City
- Optimized logistics: luminaire and driver box can be ordered separately
- Designed for versatile applications with multiple interfaces
- Robust and weatherproof: IP66 / IK08, high C5 corrosion protection for harsh environments

Product features

- Wide voltage range: 200-480V AC
- Driver efficiency: ≤97 %
- Integration: for lighting control, DMX, 0-10V dimming
- Climate membrane protects from water and lets air pass through
- Surge protection: up to 20 kV, improved safety in stadiums
- Protection: lockable driver box prevents tampering

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	1200.00 W
Nominal voltage	200…480 V
Mains frequency	0/50/60 Hz
Power factor λ	> 0.94
Protection class	I
Surge capability (L-N)	20 kV
Dimming interface	DALI-2 / DALI D4i / IoT

Dimensions & Weight

Length	487.00 mm
Width	199.00 mm
Height	105.00 mm
Product weight	6100.00 g



FL MAX PSU DA P

Materials & Colors

Product color	Gray/White aluminum
RAL Color (most similar)	RAL 9006
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-40…+50 °C
Temperature range at storage	-40…85 °C
Type of connection	Cable, 5-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK08

© 2026, LEDVANCE GmbH. All rights reserved.

Corrosion resistance class acc. to EN 12944	C5 High
Dimmable	Yes [1)]
Type of dimming	DALI D4i
Dimming range	0…100 %
IoT ready	Support of DALI data type PART 251, 252, 253 [2)]
Replaceable light source	No

1) DMX, 0-10V dimming

2) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Control gear

ECG lifetime	100000 h

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD
Ball shot safe	Yes
EPD	LEDV-00061-V02.01-EN

Additional product data

Added function	VIVARES

Accessories Optional

Product image	Product name	EAN
	FL MAX CONNECTOR BOX	4099854696176
	FL FLEX ADAPTER SOCKET ZHAGA	4099854680076
	FL FLEX ADAPTER SOCKET NEMA	4099854680113

Components for light control

Components Light Control

Product image	Product name	EAN
	MANUAL CONTROL UNIT GROUP DALI-2 TW	4099854748691

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	MANUAL CONTROL UNIT SELECT DALI-2	4058075837485
	MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508
	MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522
	MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560
	MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546
	PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075837584
	PUSH CONTROL UNIT FM DALI-2 DIM	4099854846922
	SURFACE MOUNT FRAME	4058075843561
	PUSHBUTTON COUPLER DALI-2	4058075837607
	FLEX CONTROL UNIT IOT DALI-2 HCL TW	4058075841888
	FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901
	FLEX CONTROL UNIT DALI-2 TW	4058075843844

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925
	SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621
	SENSOR CEILING MOUNTING KIT LIGHT/PRESENCE-6	4099854748714
	SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949
	SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868
	SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882
	HIGHBAY SENSOR DALI-2 LIGHT/PRESENCE -21 INFRARED CEILING MOUNTING	4058075857537
	DALI sensors -8 IR CI, -40X5 IR CI, -24 IR CM, -21 IR CM	4058075843905
	RELAY DALI-2 RAIL MOUNTING	4099854709159
	RELAY DALI-2 CEILING MOUNTING	4099854709135
	REPEATER DALI-2 RAIL MOUNTING	4099854709111
	REPEATER DALI-2 CEILING MOUNTING	4099854709098

© 2026, LEDVANCE GmbH. All rights reserved.

EQUIPMENT / ACCESSORIES

- Cable glands included and preinstalled in the power supply
- One FL MAX CONNECTOR BOX is required per separately mounted luminaire head and power supply

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	FLOODLIGHT MAX GEN 2
PDF	Legal information	Safety Insert G11205497
PDF	Legal information	G11251566 legal insert
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	FLOODLIGHT MAX GEN 2
PDF	Declarations of conformity UKCA	FLOODLIGHT MAX GEN 2
PDF	Certificates	ENEC FLOODLIGHT MAX GEN 2
PDF	EU Data Act	DALI LED Driver and Luminaires
PDF	EPD	ENVIRONMENTAL PRODUCT DECLARATION FLOODLIGHT MAX GEN 2

	Tender texts	Document name
TXT	Tender documents	FLOODLIGHT MAX POWER SUPPLY 1200W WAL-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854681653	Shipping box 1	567 mm x 257 mm x 154 mm	6570.00 g	22.44 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2026, LEDVANCE GmbH. All rights reserved.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.