PRODUCT DATASHEET
Orbis Remote-CCT 410mm 25W

Orbis CCT-DIM | LED luminaire with CCT function via wall switch or remote control with CCT and dimming



Areas of application

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

Product benefits

- Very homogenous light
- Easy and quick installation

Product features

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Remote-CCT version: color temperature, dimming, timer, memory and night functions via remote control
- Click-CCT version: color temperature adjustable in three steps by repeated switching



© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	25.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	171 mA
Inrush current	7.76 A
Max. number of luminaires per miniature circuit breaker B16	49
Max. number of luminaires per miniature circuit breaker C10	41
Max. number of luminaires per miniature circuit breaker C16	66
Power factor λ	> 0.90
Protection class	I
Operating mode	External LED driver

Photometrical data

Luminous flux	1800 lm
Total luminous flux of contained light sources	3000 lm
Luminous efficacy	72 lm/W
Color temperature	2700…6500 K
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

Dimensions & Weight

Diameter	410 mm
Height	80.00 mm
Product weight	870.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)

© 2026, LEDVANCE GmbH. All rights reserved.

Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+70 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	25000 h [1)]
Number of switching cycles	12500

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Battery size [GMS]	AAA
Nominal voltage of battery	1.5 V
Nominal capacity of battery	1400 mAh

Emergency lighting

Type of emergency light operation	Non-maintained
Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	-

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

© 2026, LEDVANCE GmbH. All rights reserved.

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	ORBIS 3100 410 CCT
PDF	Legal information	Legal insert_G11122388
PDF	Declarations of conformity	ORBIS 410MM 25W 827-865 REMOTE-CCT LEDV

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075651777	Folding box 1	453 mm x 103 mm x 453 mm	1157.00 g	21.14 dm^3
4058075651784	Shipping box 5	532 mm x 472 mm x 459 mm	7930.00 g	115.26 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.