PRODUCT DATASHEET
DR P 200W 220-240 24V

LED DRIVER PERFORMANCE | Constant voltage LED driver



PERFOR-
MANCE
CLASS

Areas of application

- Cove lighting, even in tight spaces
- For indoor SELV installations
- Offices, shopping centers, hospitals, restaurants, hotels

Product benefits

- Perfectly matched to 24 V LED flexible strips
- Excellent price/performance ratio
- Quick and simple installation

Product features

- Available in 30 W, 60 W, 120 W, 150 W, 200 W and 250 W
- Integrated cable clamp for independent installation
- Lifetime: up to 50,000 h (at max. tc temperature)
- Type of protection: IP20
- Supply voltage: 220…240 V
- Operating frequency: 50/60 Hz
- Operated with less than 60 V: Safety extra-low voltage (SELV)
- Reversible overtemperature, overload, short-circuit and open-circuit protection

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	200.00 W
Nominal output power	200 W [1)]
Nominal voltage	220…240 V
Nominal output voltage	24 V [2)]
Input voltage range	198…264 V
Input voltage AC	198…264 V [3)]
U-OUT (working voltage)	24 V
Type of current	AC
Nominal current	1300 mA
Nominal output current	0…10400 mA
Inrush current	45.6 A
Output current tolerance	5 %
Output ripple current (120 Hz)	1 %
Mains frequency	50…60 Hz
Maximum total harmonic distortion	< 10 % [4)]
Power factor λ	≥0.95 [5)]
ECG efficiency	93 % [6)]
Device power loss	15 W [7)]
Max. ECG no. on circuit breaker 10 A (B)	2
Max. ECG no. on circuit breaker 16 A (B)	3
Max. ECG no. on circuit breaker 10 A (C)	3
Max. ECG no. on circuit breaker 16 A (C)	6
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Operating frequency	50/60 Hz
Power loss in stand-by mode	≤0.5 W

1) From 0 to 200 W
2) Maximum 24 V
3) Permitted voltage range
4) At full load, 220…240 V, 50 Hz
5) Full load at 230 V
6) At full load and 230 V
7) At maximum LED load of 200 W

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Dimensions & Weight



Length	346.00 mm
Mounting hole spacing, length	336 mm
Width	45.00 mm
Height	32.00 mm
Cable cross-section, input side	0.5…1.5 mm^2
Cable cross-section, output side	0.5…1.5 mm^2
Prewired	No
Wire preparation length, input side	7…9 mm
Wire preparation length, output side	7…9 mm
Product weight	564.00 g

Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20…+80 °C
Maximum temperature at tc test point	80 °C
Max.housing temperature in case of fault	85 °C
Temperature range in operation	-20…+45 °C
Permitted rel. humidity during operation	20…90 %

Lifespan

ECG lifetime	50000 h [1)]
Number of switching cycles	25000

1) At maximum Tc = 85 °C

Additional product data

Encapsulated	Yes

Capabilities

Dimmable	No

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Overheating protection	Yes
Overload protection	Yes
No-load proof	Yes
Short-circuit protection	Yes
Max. cable length to lamp/LED module	0,8 m
Suitable for fixtures with prot. class	II
Suitable for emergency lighting	No
Type of connection, output side	Screwless terminal

Certificates & Standards

Approval marks – approval	CE / UKCA / EAC
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384
Protection class	II
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage	-20…+85 °C

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Disconnect mains before installation.
- Do not open enclosure-housing.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	G11249204 DRIVER P 30 200
PDF	Legal information	Safety Insert G11201420
PDF	Legal information	Legal Insert G11181271
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	DR P driver
PDF	Declarations of conformity UKCA	DR P driver

	Tender texts	Document name
TXT	Tender documents	LED DRIVER PERFORMANCE 200W 220 240 24V-en

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854685934	Folding box 1	51 mm x 355 mm x 38 mm	574.00 g	0.69 dm^3
4099854685941	Shipping box 20	366 mm x 275 mm x 180 mm	11730.00 g	18.12 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.