PRODUCT DATASHEET

Vintage 1906 Globe 80 40 Heart Filament DIM 4.9W 922 Gold E27

Vintage 1906 LED CLASSIC Globe Dimmable | Dimmable LED lamps, vintage edition, classic ball shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

Product features

- LED lamps for line voltage
- Lamp made of glass
- Lifetime up to 15,000 h
- Beam angle: up to 360°
- Dimmable



TECHNICAL DATA


Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	220…240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	40 W
Nominal current	30.4 mA
Type of current	AC
Inrush current	0.23 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	208
Max. lamp number on MCB B16 A	130
Maximum total harmonic distortion	≤ 120 %
Power factor λ	≥ 0.50

Photometrical data

Luminous flux	470 lm
Luminous efficacy	95 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Comfort warm white
Color temperature	2200 K
Color rendering index Ra	90
Light color	922
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

© 2026, LEDVANCE GmbH. All rights reserved.




Spectral graph LED 2200K DIM

Light technical data

Beam angle	300 °
Warm-up time (60 %)	≤ 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	123.00 mm
Diameter	80.00 mm
Maximum diameter	80 mm
Product weight	40.00 g

Temperatures & operating conditions

Ambient temperature range	-20…+45 °C
Maximum temperature at tc test point	46 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

© 2026, LEDVANCE GmbH. All rights reserved.

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes [1)]

1) Check dimmer compatibility at ledvance.com/compatibility

Certificates & Standards

Energy efficiency class	F [1)]
Energy consumption	5.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	1906LGL80D4,9W/

LOGISTICAL DATA

Temperature range at storage	-40…+85 °C

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No

© 2026, LEDVANCE GmbH. All rights reserved.

Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Networked standby power for CLS	Not relevant
Claim of equivalent power	Yes
Length	123.00 mm
Height	80.00 mm
Width	80.00 mm
Chromaticity coordinate x	0.502
Chromaticity coordinate y	0.415
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	≥0.5
LED light source replaces a fluorescent light source	No
EPREL ID	1854799
Model number	AC58089,AC58089

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LED lamp
PDF	Declarations of conformity UKCA	LED lamp

	Photometric and lighting design files	Document name
	Spectral power distribution	Spectral graph LED 2200K DIM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075836860	Folding box 1	90 mm x 90 mm x 160 mm	68.00 g	1.30 dm^3

© 2026, LEDVANCE GmbH. All rights reserved.

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075836877	Shipping box 4	202 mm x 194 mm x 172 mm	468.00 g	6.74 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.