PRODUCT DATASHEET
HB DA P 200W 865 110DEG IP66

HIGH BAY DALI GEN 5 | High-bay DALI luminaires up to 181 lm/W and attractive UGR



PERFOR-
MANCE
CLASS

Areas of application

- Replacement for high bay luminaires with mercury vapor or metal halide lamps
- Warehouses, logistic halls
- Industry
- High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies)

Product benefits

- Improved UGR compared to previous generations, down to UGR ≤ 19 (<150W, 70°) in combination with reflector
- Energy savings of up to 70 % compared to conventional high bay luminaires
- Optimized weight and size due to compact design

Product features

- DALI versions with IoT-ready DALI-2 driver
- Different luminous flux and beam angle for mounting heights of ~ 6 m to 18 m in 4000 K or 6500 K
- Dimming range (DALI): 10…100 %
- Lifetime (L80/B10): up to 100,000 h (at 35 °C)

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	200.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	880.000 mA
Inrush current	16.7 A
Inrush current time T_{h50}	302 µs
Max. number of luminaires per miniature circuit breaker B16	9
Max. number of luminaires per miniature circuit breaker C10	8
Max. number of luminaires per miniature circuit breaker C16	12
Power factor λ	> 0.95
Maximum total harmonic distortion	< 15 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2


Photometrical data

Luminous flux	35000 lm
Luminous efficacy	175 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	≤4 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0,4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	110 °


© 2026, LEDVANCE GmbH. All rights reserved.




HB DA P 200W 865 110DEG IP66




HB DA P 200W 865 110DEG IP66 WITH REFLECTOR




HB DA P 200W 865 110DEG IP66 WITH REFRACTOR



HB DA P 200W 865 110DEG IP66



HB DA P 200W 865 110DEG IP66 WITH REFLECTOR




HB DA P 200W 865 110DEG IP66 WITH REFRACTOR

Dimensions & Weight

Diameter	321.00 mm
Height	162.00 mm
Product weight	3300.00 g
Cable length	1500 mm

© 2026, LEDVANCE GmbH. All rights reserved.



HB P

Materials & Colors

Product color	Black
Housing color	Black
RAL Color (most similar)	RAL 9005
Body material	Aluminum
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30…+50 °C
Temperature range at storage	-40…+80 °C
Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK10
Dimmable	Yes
Type of dimming	DALI-2
Mounting type	Surface/Suspended
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	120000 h [1)]

© 2026, LEDVANCE GmbH. All rights reserved.

Lifespan L80/B10 at 25 °C	100000 h [1)]
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	49000 h [1)]
Number of switching cycles	200000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Nominal output current	825 mA
Output current	825 mA
Output ripple current (100 Hz)	< 5 %

Emergency lighting

Type of Emergency Lighting (EL)	EL certified driver (0Hz / DC operation) for central battery operation included
Type of emergency operation test	None

Certificates & Standards

Standards	CE / UKCA / EAC / CB / ENEC / TÜV SÜD / EPD
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
EPD	LEDV-00032-V01.01-EN

Additional product data

Added function	VIVARES

Accessories Optional

Product image	Product name	EAN
	HB BRACKET 138	4058075844643
	HB ALU REFLECTOR 500	4058075844582
	HB PC REFRACTOR 500	4058075844629

© 2026, LEDVANCE GmbH. All rights reserved.

Components for light control

Components Light Control

Product image	Product name	EAN
	MANUAL CONTROL UNIT GROUP DALI-2 TW	4099854748691
	MANUAL CONTROL UNIT SELECT DALI-2	4058075837485
	MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508
	MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522
	MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560
	MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546
	PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075837584
	PUSH CONTROL UNIT FM DALI-2 DIM	4099854846922
	SURFACE MOUNT FRAME	4058075843561
	PUSHBUTTON COUPLER DALI-2	4058075837607

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	FLEX CONTROL UNIT IOT DALI-2 HCL TW	4058075841888
	FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901
	FLEX CONTROL UNIT DALI-2 TW	4058075843844
	FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925
	SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621
	SENSOR CEILING MOUNTING KIT LIGHT/PRESENCE-6	4099854748714
	SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949
	SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868
	SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882
	HIGHBAY SENSOR DALI-2 LIGHT/PRESENCE -21 INFRARED CEILING MOUNTING	4058075857537
	DALI sensors -8 IR CI, -40X5 IR CI, -24 IR CM, -21 IR CM	4058075843905

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	RELAY DALI-2 RAIL MOUNTING	4099854709159
	RELAY DALI-2 CEILING MOUNTING	4099854709135
	REPEATER DALI-2 RAIL MOUNTING	4099854709111
	REPEATER DALI-2 CEILING MOUNTING	4099854709098

EQUIPMENT / ACCESSORIES

- Mounting hook included
- Mounting brackets, reflectors and refractors available as separate accessory

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	HB ACC
PDF	Legal information	HB DA P
PDF	Legal information	HB DA P
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	HIGHBAY DALI P
PDF	Declarations of conformity UKCA	HIGHBAY DALI P
PDF	Certificates	ENEC HIGHBAY P DALI
PDF	EU Data Act	DALI LED Driver and Luminaires
PDF	EPD	EPD EN HIGH BAY GEN 5 DALI

© 2026, LEDVANCE GmbH. All rights reserved.

	Photometric and lighting design files	Document name
	IES file (IES)	HB DA P 200W 865 110DEG IP66
	IES file (IES)	HB DA P 200W 865 110DEG IP66 WITH REFLECTOR
	IES file (IES)	HB DA P 200W 865 110DEG IP66 WITH REFRACTOR
	LDT file (Eulumdat)	HB DA P 200W 865 110DEG IP66
	LDT file (Eulumdat)	HB DA P 200W 865 110DEG IP66 WITH REFLECTOR
	LDT file (Eulumdat)	HB DA P 200W 865 110DEG IP66 WITH REFRACTOR
	ULD file (DIALux)	HB DA P 200W 865 110DEG IP66
	ROLF file (RELUX)	HB DA P 200W 865 110DEG IP66
	UGR file (UGR table)	HB DA P 200W 865 110DEG IP66
	UGR file (UGR table)	HB DA P 200W 865 110DEG IP66 WITH REFLECTOR
	UGR file (UGR table)	HB DA P 200W 865 110DEG IP66 WITH REFRACTOR
	Light distribution curve type cone	HB DA P 200W 865 110DEG IP66
	Light distribution curve type cone	HB DA P 200W 865 110DEG IP66 WITH REFLECTOR
	Light distribution curve type cone	HB DA P 200W 865 110DEG IP66 WITH REFRACTOR
	Light distribution curve type polar	HB DA P 200W 865 110DEG IP66
	Light distribution curve type polar	HB DA P 200W 865 110DEG IP66 WITH REFLECTOR
	Light distribution curve type polar	HB DA P 200W 865 110DEG IP66 WITH REFRACTOR

	CAD/BIM files	Document name
	BIM Revit 3D	High Bay G5

© 2026, LEDVANCE GmbH. All rights reserved.

	CAD/BIM files	Document name
	CAD STEP 3D	HB G5 200


	Tender texts	Document name
	Tender documents	HIGH BAY DALI GEN 5 200W 865 110DEG IP66-EN


LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075844513	Shipping box 1	368 mm x 368 mm x 171 mm	3953.00 g	23.16 dm^3


The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION









References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.