PRODUCT DATASHEET
LED WORKLIGHT VALUE FLEX 2x30W 865

WORKLIGHT VALUE FLEX | Flexible, portable worklight with adjustable lamp heads in value class



Areas of application

- Renovation
- Garages
- Workshops
- Basement

Product benefits

- Portable worklight for flexible applications
- Individually adjustable light

Product features

- Worklight with 270° vertical and 180° horizontal swiveling head
- Each of the two luminaire heads can be switched on and off individually
- Type of protection, luminaire head and housing: IP65, Type of protection, plug: IP44

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	60.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	270.000 mA
Inrush current	7.3 A
Inrush current time T_{h50}	1.5 µs
Max. number of luminaires per miniature circuit breaker B16	42
Max. number of luminaires per miniature circuit breaker C16	42
Power factor λ	≥ 0.90
Protection class	I
Operating mode	Integrated LED driver


Photometrical data

Luminous flux	6450 lm
Total luminous flux of contained light sources	6600 lm
Luminous efficacy	108 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcm
Luminous intensity	2500 cd
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.9
Photobiological safety group acc. to EN62778	RG1
Beam angle	110 °

Dimensions & Weight

Length	427.00 mm
Width	194.00 mm
Height	304.00 mm
Product weight	2150.00 g
Cable length	1500 mm

© 2026, LEDVANCE GmbH. All rights reserved.



LED WORKLIGHT VAL FLEX 2X30W 865

Materials & Colors

Product color	Black|grey
Housing color	Black|grey
Body material	Aluminum
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+80 °C
Type of connection	Plug type F
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Standing
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h [1)]
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

© 2026, LEDVANCE GmbH. All rights reserved.

EQUIPMENT / ACCESSORIES

– 1,5m power cable for flexible installation

Safety advice

– Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	LED WORKLIGHT VAL FLEX
PDF	Legal information	Legal insert LED WORKLIGHT VAL
PDF	Declarations of conformity	LED WORKLIGHT VAL

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075831292	Folding box 1	202 mm x 242 mm x 302 mm	2359.00 g	14.76 dm^3
4058075831308	Shipping box 4	504 mm x 424 mm x 327 mm	10533.00 g	69.88 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.