PRODUCT DATASHEET
STREETLIGHT FLEX SMALL 36W 730 RV25ST ZHAGA TOP&BOTTOM WA

STREETLIGHT FLEX SMALL ZHAGA TOP&BOTTOM | Light distribution for general road lighting



CONFIGURABLE

PERFOR-MANCE CLASS

Areas of application

- Street lighting, city lighting
- Outdoor applications
- City roads, industrial roads, parking lots
- M-, C- and P-class roads acc. to EN 13201
- Pedestrian zones
- Public areas
- Industry

Product benefits

- Durable design and highest quality component selection for long lasting performance
- Quick and easy wiring, due to tool-free housing opening and push button terminal
- High light uniformity
- 5 light colors available, perfectly suited to illuminate highly diverse surroundings
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Automatic mains disconnection when opening the housing
- 5 years guarantee

Product features

- Color temperature: 2,200 K, 2,700 K, 3,000 K, 4,000 K, 5,700 K
- Light distributions optimized for streets of similar width to the pole height
- Very long lifetime (L90/B10): Up to 100,000 h (at 25 °C)
- Spigot for 48-60 mm poles included
- Adjustable spigot for both side-entry and post-top installation
- +/- 15° tilt angle adjustment without opening the housing
- High luminous efficacy: up to 180 lm/W



© 2026, LEDVANCE GmbH. All rights reserved.

- Operating temperature: -40...50 °C
- High surge protection: up to 10 kV (L/N-GND)
- Protection class: I and II
- Certificate: ENEC+, ENEC, ZD4i RoHS, SASO
- Type of protection: IP66

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	36.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Nominal current	165 mA
Inrush current	26 A
Inrush current time T_{h50}	180 µs
Max. number of luminaires per miniature circuit breaker B16	16
Max. number of luminaires per miniature circuit breaker C10	13
Max. number of luminaires per miniature circuit breaker C16	21
Power factor λ	> 0.90
Maximum total harmonic distortion	< 10 %
Protection class	II
Surge capability (L-N)	6 kV
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / DALI D4i

Photometrical data

Luminous flux	5220 lm
Luminous efficacy	145 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 70
Standard deviation of color matching	< 5 sdcm
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	165 x 55 °


© 2026, LEDVANCE GmbH. All rights reserved.



SLFLEXSMP 036W 730 RV25ST216 WAC2DX

Dimensions & Weight

Length	560.00 mm
Width	250.00 mm
Height	112.00 mm
Product weight	4900.00 g



SL FL SM P 740 RU20ST WA C2 OD

Materials & Colors

Product color	White aluminum
Housing color	White aluminum
RAL Color (most similar)	RAL 9006
Body material	Aluminum
Cover material	Glass
Light emitting surface material	Glass

© 2026, LEDVANCE GmbH. All rights reserved.

Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40…+50 °C
Temperature range at storage	-30…+80 °C
Type of connection	Screwless terminal
Type of protection	IP66
Protection class IK (shock resistance)	IK09
Corrosion resistance class acc. to EN 12944	C4
Dimmable	Yes
IoT ready	Support of DALI data type PART 251, 252, 253 [1)]
Mounting type	Side entry|post top
Mounting location	Pole
Application environment	Outdoor
Mechanically adjustable	No
With light source	Yes
Replaceable light source	Yes

1) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h [1)]
Lifespan L80/B10 at 25 °C	100000 h [1)]
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	100000 h [1)]
Number of switching cycles	100000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	700 mA
Output ripple current (100 Hz)	≤ 10 %

Sensor

Type of connection for sensor/communication module	Dual Zhaga socket (on top and bottom)

Certificates & Standards

Standards	CE / ENEC+ / ENEC / EAC / UKCA / DarkSky / EPD

© 2026, LEDVANCE GmbH. All rights reserved.

Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00059-V02.01-EN
Replaceable light source (EPREL)	Only by an expert

Additional product data

Added function	VIVARES / Configurable

Accessories Optional

Product image	Product name	EAN
	SL FLEX SPIGOT 76MM WAL	4058075552531
	SL FLEX REDUCTION 60 TO 42MM WAL	4058075552579

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	User instruction G11233148 SLFLEXSMP0 20W~164W
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	SL FLEX
PDF	Legal information	LISO Insert G11233149
PDF	Legal information	Safety Insert G11218810
PDF	Declarations of conformity	SL FLEX
PDF	Declarations of conformity UKCA	SL FLEX

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	Certificates	ENEC CERTIFICATE CLASS II SL FLEX GEN2
PDF	Certificates	ENEC PLUS CERTIFICATE CLASS II SL FLEX GEN2
PDF	EPD	ENVIRONMENTAL PRODUCT DECLARATION STREETLIGHT FLEX GEN 2

	Photometric and lighting design files	Document name
IES	IES file (IES)	SLFLEXSMP 036W 730 RV25ST216 WAC2DX
LDT	LDT file (Eulumdat)	SLFLEXSMP 036W 730 RV25ST216 WAC2DX
ULD	ULD file (DIALux)	SLFLEXSMP 036W 730 RV25ST216 WAC2DX
ROLF	ROLF file (RELUX)	SLFLEXSMP 036W 730 RV25ST216 WAC2DX
	Light distribution curve type polar	SLFLEXSMP 036W 730 RV25ST216 WAC2DX

	CAD/BIM files	Document name
RFA	BIM Revit 3D	Streetlight Flex G2
STEP	CAD STEP 3D	SL_FLEX_SM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854792373	Shipping box 1	502 mm x 330 mm x 235 mm	5735.00 g	38.93 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.