PRODUCT DATASHEET
Orbis Paris 480 mm 3XE27 Beige

Orbis Paris | Socketed ceiling luminaires with fabric ring



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Replaceable LED lamp
- Elegant design

Product features

- Decorative domestic lighting
- Ceiling luminaire with socket
- Fabric material

© 2026, LEDVANCE GmbH. All rights reserved.


TECHNICAL DATA

Electrical data

Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Diameter	480.00 mm
Height	105.00 mm
Product weight	910.00 g



ORBIS PARIS

Materials & Colors

Product color	Beige
Housing color	Beige
Body material	Steel|TC fabric|Polyvinylchlorid (PVC)
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	No

© 2026, LEDVANCE GmbH. All rights reserved.

Replaceable light source	No

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	ORBIS
PDF	Legal information	Legal Insert
PDF	Declarations of conformity	ORBIS MADRID PARIS MILAN
PDF	Declarations of conformity UKCA	ORBIS MADRID PARIS MILAN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075829046	Folding box 1	112 mm x 492 mm x 492 mm	1435.00 g	27.11 dm^3
4058075829053	Shipping box 4	506 mm x 506 mm x 475 mm	6885.00 g	121.62 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.