
PRODUCT DATASHEET
LS AY SUP -12/SMB

CONNECTOR FOR TW LED STRIPS SUPERIOR CLASS | Connectors for TW LED Strips



SUPERIOR CLASS

Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Dimensions & Weight

Length	30.0 mm
Width	6.0 mm
Height	6.0 mm
Product weight	0.3 g

Colors & materials

Product color	White

Temperatures & operating conditions

Ambient temperature range	-20…+55 °C

Certificates & Standards

Type of protection	IP67

LOGISTICAL DATA

Temperature range at storage	-20…+80 °C

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LS AY PFM_SUP_13/SMB_12/SMB

	Tender texts	Document name
TXT	Tender documents	Connectors for TW LED Strips 12SMB-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451599	BAG 2	80 mm x 120 mm x 5 mm	1.60 g	0.05 dm^3
4058075451605	Shipping box 100	120 mm x 100 mm x 120 mm	128.00 g	1.44 dm^3
4058075451612	Shipping box 1,000	525 mm x 140 mm x 270 mm	1671.00 g	19.85 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.