PRODUCT DATASHEET

Vintage 1906 Edison 5 Spiral Filament DIM 3W 618 Copper E27

Vintage 1906 LED CLASSIC SLIM FILAMENT EDISON DIMMABLE | Dimmable LED lamps, vintage edition, classic Edison bulb shape slim filament - style LED technology



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "slim-filament" technology
- Spiral slim-filament with ϕ 0.6 mm
- Straight, long slim - filament width: minimum 0.7 mm

Product features

- LED lamps for line voltage
- Lamp made of glass
- Lifetime up to 15,000 h
- Beam angle: up to 360°
- Dimmable
- Can be used directly as luminaire
- Thinner filament, better decorative effect



© 2026, LEDVANCE GmbH. All rights reserved.

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	3 W
Construction wattage	3.00 W
Nominal voltage	220…240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	5 W
Nominal current	17 mA
Type of current	AC
Inrush current	0.167 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	179
Max. lamp number on MCB B16 A	287
Maximum total harmonic distortion	120 %
Power factor λ	0.50

Photometrical data

Luminous flux	45 lm
Luminous efficacy	15 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Comfort warm white
Color temperature	1800 K
Color rendering index Ra	66
Light color	618
Standard deviation of color matching	≤ 20 sdcm
Flickering metric (Pst LM)	≤1.0
Stroboscope effect metric (SVM)	≤0.4

Light technical data

Beam angle	300 °
Warm-up time (60 %)	‹ 0.50 s
Starting time	< 0.5 s

© 2026, LEDVANCE GmbH. All rights reserved.

Dimensions & Weight



Overall length	139.00 mm
Diameter	64.00 mm
Maximum diameter	64 mm
Product weight	40.00 g

Temperatures & operating conditions

Ambient temperature range	-20…+40 °C
Maximum temperature at tc test point	60 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Copper
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes [1)]

1) Check dimmer compatibility at ledvance.com/compatibility

Certificates & Standards

Energy consumption	3.00 kWh/1000h
Type of protection	IP20

© 2026, LEDVANCE GmbH. All rights reserved.

Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

Country-specific categorizations

Order reference	1906LDISOND 3W/

LOGISTICAL DATA

Temperature range at storage	-20…+80 °C

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Standby power	0 W
Claim of equivalent power	Yes
Length	139.00 mm
Height	64.00 mm
Width	64.00 mm
Chromaticity coordinate x	0.5513
Chromaticity coordinate y	0.4153
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	≥0.5
LED light source replaces a fluorescent light source	No

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

© 2026, LEDVANCE GmbH. All rights reserved.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	On-Pack-Info	ELR - exempt lamps
PDF	Declarations of conformity	LED lamp
PDF	Declarations of conformity UKCA	LED lamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854586309	Folding box 1	69 mm x 69 mm x 179 mm	58.00 g	0.85 dm^3
4099854586316	Shipping box 4	162 mm x 154 mm x 189 mm	325.00 g	4.72 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.