PRODUCT DATASHEET
LN INV D 1500 P 52W 930 DAVR WT

LINEAR INDIVILED DIRECT 1500 DALI | Surface mounted luminaire for single or light line office application with CRI90 and DALI-2 IoT technology, 1500 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare (UGR ≤ 19) thanks to IndiviLED® optics
- High performance with CRI90 and up to 135 lm/W
- IoT-ready luminaire with DALI-2 driver, suitable for VIVARES and other Light Management Systems
- Symmetric light distribution for various application areas
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Suitable for battery emergency installations acc. to EN 60598-2-22
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color
- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separetely)

© 2026, LEDVANCE GmbH. All rights reserved.

- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm^2
- Lifetime (L80/B10): 70,000 h (at 25 °C)
- Multi Lumen function: programmable DALI-2 driver

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Nominal wattage	52 W / 48 W / 44 W / 39 W
Nominal voltage	220…240 V
Mains frequency	0/50/60 Hz
Nominal current	232…210…200…185 mA
Inrush current	25.2 A
Inrush current time T_{h50}	40 µs
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C10	23
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	> 0.90
Maximum total harmonic distortion	≤ 20 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT


Photometrical data

Luminous flux	6100 lm / 5600 lm / 5400 lm / 4850 lm
Luminous efficacy	117 lm/W / 123 lm/W / 124 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥90
Standard deviation of color matching	3 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 °
UGR	< 19

© 2026, LEDVANCE GmbH. All rights reserved.



LN INV D 1500 P 52W 930 DAVR WT 1050mA



LN INV D 1500 P 52W 930 DAVR WT


Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
52 W	3000 K	6100 lm	117 lm/W
48 W	3000 K	5600 lm	117 lm/W
44 W	3000 K	5400 lm	123 lm/W
39 W	3000 K	4850 lm	124 lm/W

Dimensions & Weight

Length	1475.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3820.00 g

© 2026, LEDVANCE GmbH. All rights reserved.



LN INV 1500 P

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+50 °C
Temperature range at storage	-20…+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	DALI-2
IoT ready	Support of DALI data type PART 251, 252, 253 [1)]
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mechanically adjustable	No
With light source	Yes
Replaceable light source	Yes

© 2026, LEDVANCE GmbH. All rights reserved.

1) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h 1)
Lifespan L80/B10 at 25 °C	70000 h 1)
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h 1)
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1050mA / 975mA / 900mA / 800 mA
Output ripple current (100 Hz)	≤ 5 %
Recommended control gear	OSRAM type OTI DALI 50/220-240/1A4 NFC L

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00027-V01.01-EN
Replaceable light source (EPREL)	Only by an expert

Additional product data

Number of illuminants	1
Added function	EVERLOOP / VIVARES / Programmable Multi Lumen

Accessories Optional

Product image	Product name	EAN
	LN INV SUSPENSION KIT WT	4099854215537
	LN INV SUSPENSION WIRE	4099854323980

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	LN INV 1500 THROUGHWIRING KIT	4099854214806
	LN INV INLINE CONNECTOR	4099854215612
	LN INV CORNER CONNECTOR WT	4099854308093
	LN INV INFILL 600 WT	4099854214882
	LN INV INFILL 1200 WT	4099854214868
	LN INV INFILL 1500 WT	4099854214844

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Upgrade and replacement components

Components Light Source

Product image	Product name	EAN
	LISOEV 1339x29 60 52W 930 S90U19 GY	4099854284830

Components Driver

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	OTi DALI 50/220...240/1A4 NFC L	4062172074988

Components for light control

Components Light Control

Product image	Product name	EAN
	MANUAL CONTROL UNIT GROUP DALI-2 TW	4099854748691
	MANUAL CONTROL UNIT SELECT DALI-2	4058075837485
	MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508
	MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522
	MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560
	MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546
	PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075837584
	PUSH CONTROL UNIT FM DALI-2 DIM	4099854846922

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	SURFACE MOUNT FRAME	4058075843561
	PUSHBUTTON COUPLER DALI-2	4058075837607
	FLEX CONTROL UNIT IOT DALI-2 HCL TW	4058075841888
	FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901
	FLEX CONTROL UNIT DALI-2 TW	4058075843844
	FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925
	SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621
	SENSOR CEILING MOUNTING KIT LIGHT/PRESENCE-6	4099854748714
	SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949
	SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868
	SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	HIGHBAY SENSOR DALI-2 LIGHT/PRESENCE -21 INFRARED CEILING MOUNTING	4058075857537
	DALI sensors -8 IR CI, -40X5 IR CI, -24 IR CM, -21 IR CM	4058075843905
	RELAY DALI-2 RAIL MOUNTING	4099854709159
	RELAY DALI-2 CEILING MOUNTING	4099854709135
	REPEATER DALI-2 RAIL MOUNTING	4099854709111
	REPEATER DALI-2 CEILING MOUNTING	4099854709098

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	LN INV D PS
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11205497
PDF	Legal information	Legal Insert G11235610

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	Legal information	LN INV D DI
PDF	Declarations of conformity	LN INV
PDF	Declarations of conformity UKCA	LN INV
PDF	EU Data Act	DALI LED Driver and Luminaires
PDF	EPD	EPD EN LINEAR INDIVILED DIRECT DALI

	Photometric and lighting design files	Document name
IES	IES file (IES)	LN INV D 1500 P 52W 930 DAVR WT 1050mA
LDT	LDT file (Eulumdat)	LN INV D 1500 P 52W 930 DAVR WT 1050mA
ULD	ULD file (DIALux)	LN INV D 1500 P 52W 930 DAVR WT
ROLF	ROLF file (RELUX)	LN INV D 1500 P 52W 930 DAVR WT
	UGR file (UGR table)	LN INV D 1500 P 52W 930 DAVR WT 1050mA
	Light distribution curve type cone	LN INV D 1500 P 52W 930 DAVR WT 1050mA
	Light distribution curve type polar	LN INV D 1500 P 52W 930 DAVR WT

	CAD/BIM files	Document name
RFA	BIM Revit 3D	Linear Indiviled G2
STEP	CAD STEP 3D	LN INV D 1500 G2

	Tender texts	Document name
TXT	Tender documents	LINEAR INDIVILED DIRECT 1500 DALI 1500 P 52W 930 DAVR WT-EN


© 2026, LEDVANCE GmbH. All rights reserved.

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854136047	Folding box 1	1,252 mm x 167 mm x 87 mm	4520.00 g	18.19 dm^3
4099854136054	Shipping box 2	1,547 mm x 187 mm x 189 mm	10640.00 g	54.68 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.


ADDITIONAL CATALOG INFORMATION




LINEAR IndiviLED® DIRECT DALI WT	DRIVER	mA	W	lm	lm/W	
LN INV D 1200 P 40W 930 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	500 600 700 800	25 30 34 40	3100 3700 4250 4800	124 123 125 120	NFC NFC NFC Preset
LN INV D 1200 P 40W 940 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	500 600 700 800	25 30 34 40	3250 3850 4450 5050	130 128 131 126	NFC NFC NFC Preset
LN INV D 1500 P 52W 930 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	800 900 975 1050	39 44 48 52	4850 5400 5800 6100	124 123 117 117	NFC NFC NFC Preset
LN INV D 1500 P 52W 940 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	800 900 975 1050	39 44 48 52	5250 5850 6000 6400	135 133 125 123	NFC NFC NFC Preset



LINEAR IndiviLED® DIRECT DALI	DRIVER	mA	W	lm	lm/W	
LN INV D 1200 P 40W 930 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	500 600 700 800	25 30 34 40	3100 3700 4250 4800	124 123 125 120	NFC NFC NFC Preset
LN INV D 1200 P 40W 940 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	500 600 700 800	25 30 34 40	3250 3850 4450 5050	130 128 131 126	NFC NFC NFC Preset
LN INV D 1500 P 52W 930 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	800 900 975 1050	39 44 48 52	4850 5400 5800 6100	124 123 117 117	NFC NFC NFC Preset
LN INV D 1500 P 52W 940 DAVR WT	OSRAM OTI DALI 50/ 220-240/ 1A4 NFC L	800 900 975 1050	39 44 48 52	5250 5850 6000 6400	135 133 125 123	NFC NFC NFC Preset





References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.