# PRODUCT DATASHEET
# TRUSYS FLEX P 50W 865 WW CL WT DALI

TRUSYS FLEX WALLWASHER | Luminaire inserts with asymmetric wallwasher light distribution, up to 175 lm/W



PERFOR-
MANCE
CLASS

## Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, hardware stores
- Discounters, supermarkets

## Product benefits

- Wall washer light distribution for directed wall illumination
- Easy installation, no tools required for connection
- Flexible application due to a range of different lumen packages and beam angles
- 5 years guarantee

## Product features

- Beam angle wall washer: 1x40°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 175 lm/W
- Fixed luminare taps
- Luminaire versions available with on-off or IoT-ready DALI-2 driver
- Steel-sheet housing
- Lens material: PMMA
- Type of protection: IP40




© 2026, LEDVANCE GmbH. All rights reserved.

# TECHNICAL DATA


## Electrical data

| | |
|---|---|
| Nominal wattage | 50.00 W |
| Nominal voltage | 220…240 V |
| Mains frequency | 0/50/60 Hz |
| Nominal current | 230.000 mA |
| Inrush current | 43.8 A |
| Inrush current time $T_{h50}$ | 188 µs |
| Max. number of luminaires per miniature circuit breaker B16 | 9 |
| Max. number of luminaires per miniature circuit breaker C10 | 7 |
| Max. number of luminaires per miniature circuit breaker C16 | 12 |
| Power factor λ | ≥0.94 |
| Maximum total harmonic distortion | ≤ 15 % |
| Protection class | I |
| Operating mode | Integrated LED driver |
| Dimming interface | DALI-2 / IoT |

## Photometrical data

| | |
|---|---|
| Luminous flux | 8600 lm |
| Luminous efficacy | 175 lm/W |
| Color temperature | 6500 K |
| Light color (designation) | Cool Daylight |
| Color rendering index Ra | ≥80 |
| Standard deviation of color matching | 3 sdcm |
| Low flicker | Yes |
| Flickering metric (Pst LM) | ≤1 |
| Stroboscope effect metric (SVM) | ≤0.4 |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 40 ° |



© 2026, LEDVANCE GmbH. All rights reserved.




TRUSYS FLEX P 50W 865 WW CL WT DALI

## Dimensions & Weight

| | |
|---|---|
| Length | 1500.00 mm |
| Width | 77.70 mm |
| Height | 39.40 mm |
| Product weight | 1750.00 g |




TRUSYS FLEX luminaire - clear

## Materials & Colors

| | |
|---|---|
| Product color | White |
| Housing color | White |
| RAL Color (most similar) | RAL 9016 |
| Body material | Steel |
| Cover material | Polymethylmethacrylate (PMMA) |


© 2026, LEDVANCE GmbH. All rights reserved.

| | |
|---|---|
| Light emitting surface material | Polymethylmethacrylate (PMMA) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

## Application & Mounting

| | |
|---|---|
| Ambient temperature range | -25…+40 °C |
| Temperature range at storage | -40…+80 °C |
| Type of connection | Plug-In connection |
| Type of protection | IP40 |
| Protection class IK (shock resistance) | IK04 |
| Dimmable | Yes |
| Type of dimming | DALI |
| IoT ready | Support of DALI data type PART 251, 252, 253 [1)] |
| Mounting type | Suspended/Surface |
| Mounting location | Mounting rail |
| Application environment | Indoor |
| Mechanically adjustable | No |
| With light source | Yes |
| Replaceable light source | No |

1) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

## Lifespan

| | |
|---|---|
| Lifespan L70/B50 at 25 °C | 100000 h [1)] |
| Lifespan L80/B10 at 25 °C | 76000 h [1)] |
| Lifespan L80/B50 at 25 °C | 89000 h |
| Lifespan L90/B10 at 25 °C | 43000 h [1)] |
| Number of switching cycles | 100000 |

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Control gear

| | |
|---|---|
| Output current | 1050 mA |
| Output ripple current (100 Hz) | < 10 % |

## Emergency lighting

| | |
|---|---|
| Type of Emergency Lighting (EL) | EL certified driver (0Hz / DC operation) for central battery operation included |
| Type of emergency operation test | None |


© 2026, LEDVANCE GmbH. All rights reserved.

## Certificates & Standards

| | |
|---|---|
| Standards | CE / CB / UKCA / ENEC / EAC |
| Luminaire with limited surface temperature, "D sign" | Yes |
| Ball shot safe | No |
| Replaceable light source (EPREL) | Not replaceable |

## Additional product data

| | |
|---|---|
| Added function | VIVARES |

## Components for light control

| Components Light Control |
|---|

| Product image | Product name | EAN |
|---|---|---|
|  | MANUAL CONTROL UNIT GROUP DALI-2 TW | 4099854748691 |
|  | MANUAL CONTROL UNIT SELECT DALI-2 | 4058075837485 |
|  | MANUAL CONTROL UNIT SELECT DALI-2 TW | 4058075837508 |
|  | MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW | 4058075837522 |
|  | MANUAL CONTROL UNIT TOUCH DALI-2 TW | 4058075837560 |
|  | MANUAL CONTROL UNIT TOUCH DALI-2 | 4058075837546 |
|  | PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW | 4058075837584 |


© 2026, LEDVANCE GmbH. All rights reserved.

| Product image | Product name | EAN |
|---|---|---|
|  | PUSH CONTROL UNIT FM DALI-2 DIM | 4099854846922 |
|  | SURFACE MOUNT FRAME | 4058075843561 |
|  | PUSHBUTTON COUPLER DALI-2 | 4058075837607 |
|  | FLEX CONTROL UNIT IOT DALI-2 HCL TW | 4058075841888 |
|  | FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW | 4058075841901 |
|  | FLEX CONTROL UNIT DALI-2 TW | 4058075843844 |
|  | FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW | 4058075841925 |
|  | SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION | 4058075837621 |
|  | SENSOR CEILING MOUNTING KIT LIGHT/PRESENCE-6 | 4099854748714 |
|  | SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION | 4058075841949 |
|  | SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION | 4058075843868 |


© 2026, LEDVANCE GmbH. All rights reserved.

| Product image | Product name | EAN |
|---|---|---|
|  | SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING | 4058075843882 |
|  | HIGHBAY SENSOR DALI-2 LIGHT/PRESENCE -21 INFRARED CEILING MOUNTING | 4058075857537 |
|  | DALI sensors -8 IR CI, -40X5 IR CI, -24 IR CM, -21 IR CM | 4058075843905 |
|  | RELAY DALI-2 RAIL MOUNTING | 4099854709159 |
|  | RELAY DALI-2 CEILING MOUNTING | 4099854709135 |
|  | REPEATER DALI-2 RAIL MOUNTING | 4099854709111 |
|  | REPEATER DALI-2 CEILING MOUNTING | 4099854709098 |

## EQUIPMENT / ACCESSORIES

– Mounting rail with fixed integrated 5- and 8-pole cable

## DOWNLOAD DATA

| | Documents and certificates | Document name |
|---|---|---|
| PDF | User instruction / safety instructions | TRUSYS FLEX DALI 865 |
| PDF | Legal information | Legal insert TRUSYS FLEX DALI |
| PDF | Legal information | LSI TRUSYS FLEX 865 DALI |
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG |


© 2026, LEDVANCE GmbH. All rights reserved.

| | Documents and certificates | Document name |
|---|---|---|
| PDF | Declarations of conformity | TRUSYS FLEX DALI |
| PDF | Declarations of conformity UKCA | TRUSYS FLEX DALI |
| PDF | Certificates | ENEC Certificate Trusys Flex DALI |
| PDF | EU Data Act | DALI LED Driver and Luminaires |

| | Photometric and lighting design files | Document name |
|---|---|---|
| IES | IES file (IES) | TRUSYS FLEX P 50W 865 WW CL WT DALI |
| LDT | LDT file (Eulumdat) | TRUSYS FLEX P 50W 865 WW CL WT DALI |
| ULD | ULD file (DIALux) | TRUSYS FLEX P 50W 865 WW CL WT DALI |
| ROLF | ROLF file (RELUX) | TRUSYS FLEX P 50W 865 WW CL WT DALI |
| | Light distribution curve type polar | TRUSYS FLEX P 50W 865 WW CL WT DALI |

| | CAD/BIM files | Document name |
|---|---|---|
| RFA | BIM Revit 3D | TRUSYS FLEX |
| STEP | CAD STEP 3D | TruSys FLEX |

| | Tender texts | Document name |
|---|---|---|
| TXT | Tender documents | TRUSYS FLEX WALLWASHER 50W 865 WW CL WT DALI-EN |


## LOGISTICAL DATA


| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4099854191411 | Folding box<br>1 | 108 mm x 1,534 mm x 102 mm | 1925.00 g | 16.90 $dm^3$ |
| 4099854191428 | Shipping box<br>4 | 1,547 mm x 218 mm x 231 mm | 9620.00 g | 77.90 $dm^3$ |


The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.



© 2026, LEDVANCE GmbH. All rights reserved.


## ADDITIONAL CATALOG INFORMATION









## References / Links

– For Guarantee see www.ledvance.com/guarantee

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.


© 2026, LEDVANCE GmbH. All rights reserved.