
PRODUCT DATASHEET
LS AY VAL -SE/P + SILICONE SEAL

CONNECTORS FOR RGB LED STRIP VALUE CLASS | Connectors for RGB LED Strips



VALUE CLASS

Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Dimensions & Weight

Length	14.00 mm
Width	10.0 mm
Height	6.0 mm
Product weight	1.00 g

Colors & materials

Product color	Transparent

Temperatures & operating conditions

Ambient temperature range	-15…+50 °C
Temperature range in operation	-15…+50 °C

Certificates & Standards

Type of protection	IP65

LOGISTICAL DATA

Temperature range at storage	-20…+85 °C

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	CE declaration LS AY VAL

	Tender texts	Document name
TXT	Tender documents	Connectors for RGB LED Strips SEP SILICONE SEAL-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407985	BAG 4	80 mm x 120 mm x 5 mm	2.00 g	0.05 dm^3
4058075407992	Shipping box 200	180 mm x 100 mm x 180 mm	329.00 g	3.24 dm^3
4058075408005	Shipping box 2,000	520 mm x 380 mm x 210 mm	4057.00 g	41.50 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2026, LEDVANCE GmbH. All rights reserved.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.