
PRODUCT DATASHEET
OT 75/170-240/1A0 4DIM NFC G3 CE

OPTOTRONIC 4DIM NFC IP20 | Constant Current - Outdoor - dimmable



Areas of application

- Street and urban lighting
- Industry
- Suitable for outdoor applications in luminaires with IP > 54
- Suitable for use in outdoor luminaires of protection class I and II

Product benefits

- 4DIM functionality in one device (StepDIM, AstroDIM, MainsDIM, DALI)
- DALI-2 certified incl. Parts 251, 252, 253
- Easy and fast wireless luminaire programming
- High surge protection: up to 10 kV (in protection class I or II)
- Great flexibility due to wide operating temperature range of -40…55 °C or 60 °C
- High surge DALI protection: 1 kV
- Protection through double isolation between mains input and LED output
- Optimized NFC for programming from the top: easy accessibility in luminaires

Product features

- Supply voltage: 220…240 V
- Wide current output range: 150 mA…1050 mA or 1500 mA
- Easy and fast wireless luminaire programming via NFC
- Flexible current setting with one additional wire (LEDset2)
- AstroDIM for autonomous dimming with five independent levels (astro, time mode)
- Allows for energy saving in twilight phases
- MainsDIM function for dimming via reduction of line voltage amplitude
- Isolated DALI interface for bidirectional telemanagement systems
- Standby power consumption: < 0.35 W
- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	75.00 W
Nominal output power	75 W [1]
Nominal voltage	220…240 V
Nominal output voltage	35…115 V
Input voltage range	220…277 V
Input voltage AC	170…264 V [2]
Input voltage DC	176…276 V [3]
U-OUT (working voltage)	120 V
Nominal current	1.05 A
Nominal output current	150…1050 mA
Inrush current	62 A [4]
Output current tolerance	3 % [5]
Output ripple current (100 Hz)	> 4 %
Mains frequency	0/50/60 Hz
Maximum total harmonic distortion	> 5 % [6]
Power factor λ	0.99 [7]
ECG efficiency	92 % [8]
Device power loss	6.5 W
Max. ECG no. on circuit breaker 10 A (B)	6
Max. ECG no. on circuit breaker 16 A (B)	10
Max. ECG no. on circuit breaker 25 A (B)	16
Surge capability (L/N-Ground)	10 kV
Surge capability (L-N)	6 kV
Galvanic isolation	SELV
Flickering metric (Pst LM)	≤1


1) Max. 75% in DC operating mode
2) Permitted voltage range
3) Additional fuse needed in DC operation
4) At 202 µs
5) +/- 5% for LEDset down to 150mA
6) At full power
7) At full load
8) at 230 V, 50 Hz

Photometrical data

Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

© 2026, LEDVANCE GmbH. All rights reserved.

Dimensions & Weight



Length	123.00 mm
Mounting hole spacing, length	111,0 mm
Width	79.00 mm
Height	33.00 mm
Cable cross-section, input side	0.2…1.5 mm^2
Cable cross-section, output side	0.2…1.5 mm^2
Wire preparation length, input side	8.5…9.5 mm
Wire preparation length, output side	8.5…9.5 mm
Product weight	210.00 g

Colors & materials

Product color	Black
Casing material	Plastic
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-40…+55 °C
Maximum temperature at tc test point	90 °C
Max.housing temperature in case of fault	120 °C
Permitted rel. humidity during operation	5...95 % [1)]

1) The luminaire manufacturer must ensure that condensation water cannot be created within the fixture.

Lifespan

ECG lifetime	50000 h / 100000 h [1)]

1) At maximum T_C = 80°C / 10% failure rate / At T_C = 68°C / 10% failure rate

Capabilities

Dimmable	Yes
Dimming interface	4DIM / AstroDIM / DALI / MainsDIM / StepDIM

© 2026, LEDVANCE GmbH. All rights reserved.

Dimming range	10…100 %
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m [1)]
Suitable for fixtures with prot. class	I / II
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

1) Output wires must be routed as close as possible to each other

Certificates & Standards

Approval marks – approval	CCC / CE / DALI-2 / EL / ENEC / RCM / VDE
Standards	Acc. to EN 61347-1 / Acc. to ENEC 61347-2-13 / Acc. to EN 62384 / Acc. to EN 55015:2006 + A1:2007 + A2:2009 / Acc. to EN 61547 / Acc. to FCC 47 part 15 class B / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 62386-101 / Acc. to IEC 62386-102 / Acc. to IEC 62386-207 / UL-8750
Protection class	I/II
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage	-40…+85 °C

Energy labelling regulation data acc EU 2019/2015

Networked standby power for CLS	0.35 W

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	OT 110/165/40/75 /170-240/1A0 4DIM
PDF	Declarations of conformity	OT 110/165/40/75 /170-240/1A0 4DIM
PDF	Declarations of conformity UKCA	OT 110/165/40/75 /170-240/1A0 4DIM
PDF	Certificates	OT 110/165/40/75 /170-240/1A0 4DIM

© 2026, LEDVANCE GmbH. All rights reserved.

	Documents and certificates	Document name
PDF	Certificates	OT 110/170-240/1A0 4DIM NFCG3CE
PDF	Certificates	OT 75/170-240/1A0 4DIM NFC G3CE
PDF	Certificates	OT 75/170-240/1A0 4DIM NFC G3CEVS18
PDF	EU Data Act	Connected Products and Related Software and Services

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172218993	Unpacked 1	123 mm x 79 mm x 33 mm	210.00 g	0.32 dm^3
4062172279871	Shipping box 18	272 mm x 260 mm x 125 mm	4152.00 g	8.84 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.