PRODUCT DATASHEET
SF FLAT SQ 330 P 19W ML 83040

SURFACE FLAT SQUARE | Versatile square wall and ceiling luminaire



Areas of application

- Direct replacement for surface luminaires with integrated CFLni lamps
- Corridors
- Stairways
- Bathrooms
- Foyers

Product benefits

- Easy upgradeability of light source, driver and sensor (EVERLOOP design)
- Highly versatile due to selectable CCT and lumen steps (Multi Select) on the driver
- Indoor luminaire with high luminous efficacy up to 140 lm/W
- High color consistency with SDCM 3
- Tool-free electrical connection due to push button connector
- Very homogenous light with a slight backlight effect
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- 5 years guarantee

Product features

- Type of protection: IP54 (wall and ceiling)
- Impact resistance: IK08
- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- Polycarbonate (PC) housing, PC-diffuser
- Ambient temperature in operation: -20…+45 °C
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm^2
- Through-wiring possible

© 2026, LEDVANCE GmbH. All rights reserved.

- Indoor use only, not suitable for outdoor use
- Sensor version with high frequency sensor, corridor- and grouping function

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	19 W / 12 W [1)]
Nominal voltage	220…240 V
Mains frequency	50/60 Hz
Nominal current	85.000 mA
Inrush current	13 A
Inrush current time T_{h50}	112 µs
Max. number of luminaires per miniature circuit breaker B16	57
Max. number of luminaires per miniature circuit breaker C10	46
Max. number of luminaires per miniature circuit breaker C16	73
Power factor λ	> 0.90
Maximum total harmonic distortion	< 20 %
Protection class	II
Operating mode	Integrated LED driver


1) For possible options refer to lumen/power table image

Photometrical data


Luminous flux	2660 lm / 1660 lm [1)]
Luminous efficacy	140 lm/W / 138 lm/W [1)]
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	3 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

1) For possible options refer to lumen/power table image


© 2026, LEDVANCE GmbH. All rights reserved.




SF FLAT SQ 330 P 19W 3000K 2490lm



SF FLAT SQ 330 P 19W 4000K 2660lm




SF FLAT SQ 330 P 19W 3000K 2490lm



SF FLAT SQ 330 P 19W 4000K 2660lm

Dimensions & Weight

Length	330.00 mm
Width	330.00 mm
Height	65.00 mm
Product weight	1529.00 g



SF FLAT SQ 330 19W CPS

Materials & Colors

Product color	White
Housing color	White

© 2026, LEDVANCE GmbH. All rights reserved.

RAL Color (most similar)	RAL 9003
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+45 °C
Temperature range at storage	-40…+80 °C
Type of connection	Screwless terminal
Type of protection	IP54
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h [1)]
Lifespan L80/B10 at 25 °C	100000 h [1)]
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h [1)]
Number of switching cycles	100000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	450 mA
Output ripple current (100 Hz)	< 5 %

Emergency lighting

Type of Emergency Lighting (EL)	EL certified driver (0Hz / DC operation) for central battery operation included

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD

© 2026, LEDVANCE GmbH. All rights reserved.

Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
EPD	LEDV-00028-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	EVERLOOP / MULTI LUMEN / MULTI COLOR

Accessories Optional

Product image	Product name	EAN
	LISOEV 330 SQ 19W 830 840 SF FLAT	4099854312250
	SF FLAT 330 SQUARE FRAME SI	4099854292910
	DR DS SENS-P- 19/220-240/450 SF FL	4099854292859
	SENSOR SF FLAT LEADER FOLLOWER	4099854292897

EQUIPMENT / ACCESSORIES

- EVERLOOP luminaire: upgrades and replacements available
- Decorative silver frame separately available

Upgrade and replacement components

Components Light Source

Product image	Product name	EAN
	LISOEV 330 SQ 19W 830 840 SF FLAT	4099854312250

Components Driver

© 2026, LEDVANCE GmbH. All rights reserved.

Product image	Product name	EAN
	DR DS SENS-P- 19/220-240/450 SF FL	4099854292859

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI Surface Flat
PDF	User instruction / safety instructions	SEN SF FLAT LEADER FOLLOWER
PDF	Legal information	LISO Insert SF FLAT
PDF	Legal information	Legal Insert SF FLAT
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11218810
PDF	Declarations of conformity	CE Declaration SF FLAT
PDF	Declarations of conformity UKCA	UKCA Declaration SF FLAT
PDF	Certificates	ENEC SF FLAT
PDF	EPD	EPD EN SURFACE FLAT

	Photometric and lighting design files	Document name
IES	IES file (IES)	SF FLAT SQ 330 P 19W 3000K 2490lm
IES	IES file (IES)	SF FLAT SQ 330 P 19W 4000K 2660lm
LDT	LDT file (Eulumdat)	SF FLAT SQ 330 P 19W 3000K 2490lm
LDT	LDT file (Eulumdat)	SF FLAT SQ 330 P 19W 4000K 2660lm
ULD	ULD file (DIALux)	SF FLAT SQ 330 P 19W CPS

© 2026, LEDVANCE GmbH. All rights reserved.

	Photometric and lighting design files	Document name
	ROLF file (RELUX)	SF FLAT SQ 330 P 19W CPS
	UGR file (UGR table)	SF FLAT SQ 330 P 19W 3000K 2490lm
	UGR file (UGR table)	SF FLAT SQ 330 P 19W 4000K 2660lm
	Light distribution curve type cone	SF FLAT SQ 330 P 19W 3000K 2490lm
	Light distribution curve type cone	SF FLAT SQ 330 P 19W 4000K 2660lm
	Light distribution curve type polar	SF FLAT SQ 330 P 19W 3000K 2490lm
	Light distribution curve type polar	SF FLAT SQ 330 P 19W 4000K 2660lm

	CAD/BIM files	Document name
	BIM Revit 3D	Surface Flat
	CAD STEP 3D	SF FLAT SQ 330

	Tender texts	Document name
	Tender documents	SURFACE FLAT SQUARE 330 P 19W CPS-EN


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854292491	Folding box 1	72 mm x 336 mm x 336 mm	1725.00 g	8.13 dm^3
4099854292507	Shipping box 6	448 mm x 353 mm x 358 mm	11013.00 g	56.62 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2026, LEDVANCE GmbH. All rights reserved.


ADDITIONAL CATALOG INFORMATION





SF FLAT RD / SQ	DRIVER	CCT	W	lm	lm/W	EM W 230V DC	EM lm 230V DC	EM lm/W 230V DC
SF FLAT 330	DR DS SENS- P-19/220-240/650 SF FL EAN 4099854292858	4000K	19 12	2660 1680	140 138	-	-	-
SF FLAT SEN 330		3000K	19 12	2480 1560	131 130	-	-	-
SF FLAT 500	DR DS-SENS- P-27/220-240/650 SF FL EAN 4099854292873	4000K	27 19	3780 2660	140 140	-	-	-
SF FLAT SEN 500		3000K	27 19	3600 2530	133 133	-	-	-
SF FLAT DALI 500	DR DALI 50/220...240/1A4 NFC EAN 4062172061884	4000K	27	3780	140	5.5	510	92
		3000K	27	3600	133	5.5	500	90



www.ledvance.com/everloop-replacement







References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.