# PRODUCT DATASHEET
# LED STICK 95 11W 840 FROSTED E27

LED CLASSIC STICK V | LED lamps with classic stick shape with housing consisting of min. 50% recycled plastics




VALUE CLASS

## Areas of application


- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Outdoor use in suitable outdoor luminaires only

## Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Attractive lamp appearance
- Instant 100 % light, no warm-up time

## Product features

- LED alternative to conventional lamps
- Lifetime up to 15,000 h
- Not dimmable
- Minimum 50 % of recycled plastic (out of total plastic weight) used
- Good quality of light; color rendering index $R_a$: ≥ 80; constant chromaticity



# TECHNICAL DATA


## Electrical data

| | |
|---|---|
| Nominal wattage | 11 W |
| Construction wattage | 11.00 W |
| Nominal voltage | 220…240 V |
| Operating mode | AC Mains |
| Claimed equiv. conventional lamp power | 95 W |
| Nominal current | 85 mA |
| Type of current | AC |
| Inrush current | 6.8 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 49 |
| Max. lamp number on MCB B16 A | 61 |
| Maximum total harmonic distortion | 119 % |
| Power factor λ | 0.60 |

## Photometrical data

| | |
|---|---|
| Luminous flux | 1470 lm |
| Luminous efficacy | 133 lm/W |
| Lumen main.fact.at end of nom.life time | 0.93 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | 80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdcm |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.4 |


© 2026, LEDVANCE GmbH. All rights reserved.




EPREL Data Spectral Diagram LEDr _4000K

## Light technical data

| | |
|---|---|
| Beam angle | 240 ° |
| Warm-up time (60 %) | 0.50 s |
| Starting time | 0.5 s |

## Dimensions & Weight




| | |
|---|---|
| Overall length | 117.00 mm |
| Diameter | 40.00 mm |
| Maximum diameter | 40 mm |
| Product weight | 35.00 g |

## Temperatures & operating conditions

| | |
|---|---|
| Ambient temperature range | -40…+40 °C |
| Maximum temperature at tc test point | 90 °C |


© 2026, LEDVANCE GmbH. All rights reserved.

## Lifespan

| | |
|---|---|
| Lifespan L70/B50 at 25 °C | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.93 |

## Additional product data

| | |
|---|---|
| Base (standard designation) | E27 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Frosted |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

## Capabilities

| | |
|---|---|
| Dimmable | No |

## Certificates & Standards

| | |
|---|---|
| Energy efficiency class | E [1)] |
| Energy consumption | 11.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG0 |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

## Country-specific categorizations

| | |
|---|---|
| Order reference | LED STICK95 11W |

## LOGISTICAL DATA

| | |
|---|---|
| Temperature range at storage | -40…+80 °C |

## Energy labelling regulation data acc EU 2019/2015

| | |
|---|---|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | E27 |
| Connected light source (CLS) | No |


© 2026, LEDVANCE GmbH. All rights reserved.

| | |
|---|---|
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Standby power | 0.00 W |
| Claim of equivalent power | Yes |
| Length | 117.00 mm |
| Height | 40.00 mm |
| Width | 40.00 mm |
| Chromaticity coordinate x | 0.3818 |
| Chromaticity coordinate y | 0.3797 |
| R9 Colour rendering index | 1 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | 0.864 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 2190104 |
| Model number | AC69386,AC69386,AC69386 |

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## DOWNLOAD DATA

| | Documents and certificates | Document name |
|---|---|---|
| PDF | Declarations of conformity | Declaration of conformity CE FTL Sticks |
| PDF | Declarations of conformity | Declaration of conformity CE |
| PDF | Declarations of conformity UKCA | UKCA declaration LED stick |

| | Photometric and lighting design files | Document name |
|---|---|---|
| | Spectral power distribution | EPREL Data Spectral Diagram LEDr _4000K |


© 2026, LEDVANCE GmbH. All rights reserved.

## LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4099854483851 | Folding box<br>1 | 42 mm x 42 mm x 121 mm | 48.00 g | 0.21 $dm^3$ |
| 4099854483868 | Shipping box<br>10 | 218 mm x 92 mm x 132 mm | 552.00 g | 2.65 $dm^3$ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.


© 2026, LEDVANCE GmbH. All rights reserved.