
PRODUCT DATASHEET
LS AY -CSW/P2/50

CONNECTORS FOR LED STRIPS PERFORMANCE AND VALUE CLASS | Connector for LED Strips



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	5000 mA

Dimensions & Weight

Length	82 mm
Cable length	50 mm
Width	10.5 mm
Height	4.5 mm
Cable cross-section, input side	0.5 mm^2
Product weight	4.00 g

Colors & materials

Product color	White

Temperatures & operating conditions

Ambient temperature range	-20…+55 °C

Certificates & Standards

Type of protection	IP00

LOGISTICAL DATA

Temperature range at storage	-20…+80 °C

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LS AY

	Tender texts	Document name
TXT	Tender documents	Connectors for LED Strips PFM and VAL CSWP250-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727434	BAG 2	80 mm x 120 mm x 5 mm	9.00 g	0.05 dm^3
4058075727441	Shipping box 100	180 mm x 100 mm x 180 mm	529.00 g	3.24 dm^3

© 2026, LEDVANCE GmbH. All rights reserved.

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727458	Shipping box 1,000	520 mm x 380 mm x 210 mm	6058.00 g	41.50 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.