PRODUCT DATASHEET
OTi DALI 50/220…240/1A4 LT2 L G2

OPTOTRONIC® Intelligent | – Dimmable DALI SELV LEDset (LT2)



Areas of application

- Linear lighting for office, education, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I

Product benefits

- Fully programmable via software (DALI Interface)
- Flexible current setting (LEDset2)
- Lifetime: up to 100,000 h (temperature at T_C = 65 °C, max. 10 % failure rate)
- High-quality dimming of 1…100 % by amplitude dimming (except 80 W versions)
- High quality of light thanks to <1% output ripple current
- Very high efficiency
- Very low standby power consumption: < 0.15 W *
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

Versatile scope of application due to OSRAM DALI Technology:

- Easy to use in corridors and restrooms because of three-level Corridor function
- Touch DIM application: easy to control via pushbutton or sensor
- Energy efficient Touch DIM operation due to automatic switch-off at sufficient residual light
- Suitable for emergency Installations (acc. to EN 60598-2-22 and IEC 61347-2-13, appendix J) thanks to DC detection (0 Hz, pulsating DC), on/off switchable
- Feedback of power consumption and operating hours (Fit for SMART GRID)
- Suitable for buildings according to EPBD/BREEAM/LEED due to automatic Constant Lumen Output setting
- Luminaire information for easy maintenance

Product features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile DALI window driver up to 80 W due to flexible output characteristic
- Supply voltage: 220…240 V

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

- Available with output current range: up to 2,100 mA
- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)
- DALI-2 certified (Part -101,-102 and -207)

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data


Nominal wattage	54.00 W
Nominal output power	12…50 W
Nominal voltage	220…240 V
Nominal output voltage	15…54 V
Input voltage AC	198…264 V
Input voltage DC	176…276 V
U-OUT (working voltage)	< 60 V
Nominal output current	600…1400 mA
Inrush current	20 A
Output current tolerance	3 % [1)]
Output ripple current (100 Hz)	< 1 %
Mains frequency	0/50/60 Hz
Maximum total harmonic distortion	< 15 %
Power factor λ	> 0.95
ECG efficiency	91 %
Device power loss	6 W
Max. ECG no. on circuit breaker 10 A (B)	13
Max. ECG no. on circuit breaker 16 A (B)	20
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Power loss in stand-by mode	< 0.15 W
Flickering metric (Pst LM)	≤1

1) When use DALI

Photometrical data

Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

Dimensions & Weight



© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Length	360.00 mm
Mounting hole spacing, length	350,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.5…1.5 mm^2
Cable cross-section, output side	0.5…1.5 mm^2
Wire preparation length, input side	8.0…9.0 mm
Wire preparation length, output side	8.0…9.0 mm
Product weight	240.00 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-25…+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5…85 % [1)]

1) Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h / 100000 h [1)]

1) At maximum T_C = 75°C / 10% failure rate / At T_C = 65 °C / 10 % failure rate

Additional product data

Encapsulated	No

Capabilities

Dimmable	Yes
Dimming interface	DALI-2 / Touch DIM / Touch DIM Sensor
Dimming range	1…100 %
Overheating protection	Automatic reversible
Overload protection	Non-reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	I
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Certificates & Standards

Approval marks – approval	CE / EL / ENEC 10 / VDE-EMC / CCC / RCM
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384 / Acc. to EN 62386
Protection class	I
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage	-40…+85 °C

Energy labelling regulation data acc EU 2019/2015

Networked standby power for CLS	0.17 W

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	OPTOTRONIC LED Power Supply
PDF	Declarations of conformity	INOTEC-Conformity declaration AN00954 OTI DALI 50/220-240/1A4 LT2 L G2
PDF	Declarations of conformity	EU Declaration of Conformity 3634324 (EN)
PDF	Declarations of conformity	INOTEC- Conformity declaration AM06314_OTiDALI50_220-240_1A4_LT2_L_G2
PDF	Declarations of conformity	EATON(CEAG)-Conformity declaration AN00954 OTI DALI 50/220-240/1A4 LT2 L G2
PDF	Declarations of conformity	EATON(CEAG)-Conformity declaration AM06314_OTiDALI50_220-240_1A4_LT2_L_G2
PDF	Certificates	OTI DALI LT2 L G2 CB DE1 60134 040320
PDF	Certificates	VDE EMC Certificate 40038827
PDF	Certificates	VDE ENEC Certificate 40038447
PDF	EU Data Act	Connected Products and Related Software and Services

	CAD/BIM files	Document name
STEP	CAD STEP 3D	OTi DALI L G2
ZIP	CAD data 3D PDF	CAD data PDF OTI DALI 35,50/LT2 L G2

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899551787	Unpacked 1			
4052899551794	Shipping box 20	385 mm x 160 mm x 100 mm	5071.00 g	6.16 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.